

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Reno</u>		<u>SE</u> $\frac{1}{4}$ <u>NW</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$	<u>14</u>	T <u>23</u> S	R <u>6</u> EW
Distance and direction from nearest town or city street address of well if located within city? <u>702 W 2nd in Hutchinson</u>					
2 WATER WELL OWNER: <u>E + M Plumbing</u>					
RR#, St. Address, Box # : <u>702 W 2nd</u>					
City, State, ZIP Code : <u>Hutch, KS 67501</u>					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>40</u> ft. ELEVATION:			
A 2x2 grid representing a section box. The quadrants are labeled NW, NE, SW, SE. An 'X' is drawn in the NE quadrant.		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>10</u> ft. below land surface measured on mo/day/yr <u>9-13-96</u>			
		Pump test data: Well water was <u>11</u> ft. after <u>12</u> hours pumping <u>25</u> gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>8</u> in. to <u>43</u> ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial <u>Lawn and garden only</u> 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No... <u>X</u> If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? <u>Yes</u> No			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
2 PVC		4 ABS		6 Asbestos-Cement	
				7 Fiberglass	
Blank casing diameter <u>5</u> in. to <u>30</u> ft., Dia				8 Concrete tile	
Casing height above land surface <u>12</u> in., weight <u>2.29</u> lbs./ft.				9 Other (specify below)	
TYPE OF SCREEN OR PERFORATION MATERIAL:				CASING JOINTS: Glued <u>X</u> Clamped	
1 Steel		3 Stainless steel		7 Welded	
2 Brass		4 Galvanized steel		8 Threaded	
SCREEN OR PERFORATION OPENINGS ARE:				10 Asbestos-cement	
1 Continuous slot		3 Mill slot		11 Other (specify)	
2 Louvered shutter		4 Key punched		12 None used (open hole)	
SCREEN-PERFORATED INTERVALS:				8 Saw cut	
From <u>30</u> ft. to <u>40</u> ft., From				9 Drilled holes	
GRAVEL PACK INTERVALS:				10 Other (specify)	
From <u>21</u> ft. to <u>43</u> ft., From					
FROM		TO		LITHOLOGIC LOG	
0		5		Br & Gr Clay	
5		43		Sand & Gravel	
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout		3 Bentonite	
Grout Intervals: From <u>1</u> ft. to <u>21</u> ft., From				4 Other	
What is the nearest source of possible contamination:				10 Livestock pens	
1 Septic tank		4 Lateral lines		11 Fuel storage	
2 Sewer lines		5 Cess pool		12 Fertilizer storage	
3 Watertight sewer lines		6 Seepage pit		13 Insecticide storage	
Direction from well? <u>E</u>				14 Abandoned water well	
				15 Oil well/Gas well	
				16 Other (specify below)	
				How many feet? <u>100</u>	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>9-13-96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>447</u> This Water Well Record was completed on (mo/day/yr) <u>10-12-96</u> under the business name of <u>Miller Drilling</u> by (signature) <u>G Miller</u>					