

1 LOCATION OF WATER WELL: Fraction NE 1/4 SW 1/4 NE 1/4 Section Number 4 Township Number T 23 S Range Number R 6 E
 County: Leawards
 Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: Dave Childs
 RR#, St. Address, Box #: Sycamore
 City, State, ZIP Code: Leawards KS 67501
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION: 8 ft.
 Depth(s) Groundwater Encountered 1. 8 ft. 2. 8 ft. 3. 8 ft.
 WELL'S STATIC WATER LEVEL 8 ft. below land surface measured on mo/day/yr 7-11-96
 Pump test data: Well water was 10 ft. after 10 hours pumping 20 gpm
 Est. Yield 20 gpm: Well water was 10 ft. after 10 hours pumping 20 gpm
 Bore Hole Diameter 12 in. to 30 ft., and 30 in. to 30 ft.
 WELL WATER TO BE USED AS:
☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
☐ 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
☒ PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 Blank casing diameter 5 in. to 25 ft. Dia. 50 in. to 50 ft. Dia. 50 in. to 50 ft.
 Casing height above land surface 14 in., weight 50 lbs./ft. Wall thickness or gauge No. 26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 3 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 25 ft. to 30 ft. From 25 ft. to 30 ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 30 ft. From 20 ft. to 30 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 20 ft. From 20 ft. to 30 ft. From 30 ft. to 30 ft.
 What is the nearest source of possible contamination:
☒ Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? SW How many feet? 100

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-20-96 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 440 This Water Well Record was completed on (mo/day/yr) 7-10-97
 under the business name of Carl Vincent Sany by (signature) Carl Vincent Sany

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.