

[1] LOCATION OF WATER WELL:		Fraction	Township Number	Range Number				
County: Reno		NE ¼ SE ¼ SE ¼	3 T 23 S	R 6 E W				
Distance and direction from nearest town or city street address of well if located within city? 2113 N Hendricks in Hutchinson								
[2]	WATER WELL OWNER: Mike Gore RR#, St. Address, Box #: 2113 N Hendricks City, State, ZIP Code: Htch, KS 67502		Board of Agriculture, Division of Water Resources Application Number:					
[3]	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:							
<div style="text-align:center;">N <table border="1" style="margin:auto; width:150px; height:150px;"><tr><td>NW</td><td>NE</td></tr><tr><td>SW</td><td>SE X</td></tr></table> S E</div>		NW	NE	SW	SE X	DEPTH OF COMPLETED WELL 40 ft. ELEVATION: Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 11 ft. below land surface measured on mo/day/yr 7-8-97 Pump test data: Well water was 15 ft. after 1/2 hours pumping 30 gpm Est. Yield gpm Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 43 ft., and in. to ft.		
		NW	NE					
SW	SE X							
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No...K; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes K No								
[5]	TYPE OF BLANK CASING USED:		CASING JOINTS: Glued P Clamped					
1 Steel 3 RMP (SR)		5 Wrought iron	Concrete tile					
(2) PVC 4 ABS		6 Asbestos-Cement	Other (specify below)					
Blank casing diameter 5 in. to 30 ft., Dia in. to ft., Dia in. to ft.		7 Fiberglass	Threaded					
Casing height above land surface 12 in., weight 2.29 lbs./ft. Wall thickness or gauge No. 160								
TYPE OF SCREEN OR PERFORATION MATERIAL:		(2) PVC	10 Asbestos-cement					
1 Steel 3 Stainless steel		5 Fiberglass	8 RMP (SR)					
2 Brass 4 Galvanized steel		6 Concrete tile	9 ABS					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	(8) Saw cut 11 None (open hole)					
1 Continuous slot 3 Mill slot		6 Wire wrapped	9 Drilled holes					
2 Louvered shutter 4 Key punched		7 Torch cut	10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 30 ft. to 40 ft., From ft. to ft.								
GRAVEL PACK INTERVALS: From 23 ft. to 43 ft., From ft. to ft.								
[6]	GROUT MATERIAL:		Neat cement Cement grout Bentonite Other					
Grout Intervals: From 2 ft. to 23 ft., From ft. to ft., From ft. to ft.								
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well						
1 Septic tank 4 Lateral lines 7 Pit privy		11 Fuel storage 15 Oil well/Gas well						
2 Sewer lines 5 Cess pool 8 Sewage lagoon		12 Fertilizer storage 16 Other (specify below)						
(3) Watertight sewer lines 6 Seepage pit 9 Feedyard		13 Insecticide storage						
Direction from well? N		How many feet? 25						
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLOGGING INTERVALS			
0	7	Sandy Br Silty						
7	43	Sand & Gravel						
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 7-8-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 447 This Water Well Record was completed on (mo/day/yr) 7-8-97 under the business name of Miller Drilling by (signature) Jmiller								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.								

1.