		16.3 **	WATE	R WELL RECO	RD Fo	m WWC-5	KSA 82a	-1212		1514
1 LOCAT	ION OF WAT		Fraction			Sec	tion Numb	er Township N	lumber	Range Number
County:		eno	NE ¼			1/4	2	т 23	S	<mark>к 6</mark> е
Distance and direction from nearest town or city street address of well if located within city? Westborough Bldg 1301 W. 30 th , Hutchinson, Kansas										
	WELL OWNE		Glaves							
RR#, St. A	ddress, Box #	: 120 S.	Market Suite	600						
City State	7IP Code	· Wichif	ta. Ks 67202					Application N	umber:	
LOCAT	E WELL'S LO	CATON WITH				30				
	IN SECTION E	SUX:	DEPTH OF C			- 30	Λ . ΕL	EVATION:		
			Depth(s) Ground				halandar	п. 2 Голибара — П. 2	π. 3	Ft.
	N									
	X	1								nping Gpm
-	NW	NE	ESt. Tield		veli water	was		FL and	Hours pur	nping Gpm > Ft.
l ∰ w L			WELL WATER T	O BE USED A	S: 5 Pu	blic water s	supply	Ft. and 8 Air conditio	ning 11 l	njection well
₹ ''			1 Domestic	3 Feed lot	6 Oi	field water	supply	9 Dewatering	12 (Other (Specify below)
	sw	SE	2 Irrigation	4 Industria	I 7 La	wn and gan	den (domes	stic) 10 Monitoring	g well AS	-5
	i	i	Was a chemical/t	acteriological	sample su	ubmitted to	Departmen	t? Yes No X	lf yes, m	o/day/yr sample was
* L			Submitted	_			-	Vater Well Disinfecte		
5 TYPE O	OF BLANK CAS	SING USED:		5 Wrought	Iron	8 Concr				Clamped
1 <u>St</u>	eel	3 RMP ((SR)	6 Asbestos	-Cement				Welded	
2 PV	/C	4 ABS		7 Fiberglas	s			Г	Threade	d X
				F 4				A 01		
Blank casin	ng diameter	4		Dia	e/		το	π., Dia	in.	toft.
TYPE OF O			N MATERIAL:	n., weight	50	<u>уп 40</u> 	Lbs./	ft. Wall thickness of 10 Asb	r gauge No.	
			ess steel	E Eiborglag						
1 Ste 2 Bra		a Galva	nized steel	6 Concrete			ABS		e used (open l	hole)
SCREEN C	DR PERFORA	TION OPENIN	IGS ARE:		4	d wrapped				None (open hole)
1	ontinuous slot	3	Mill slot			rapped		9 Drilled holes		
2 Lo	uvered shutter		Key punched	7	7 Torch of	cut		10 Other (spec	ify)	
SCREEN-P	PERFORATED	INTERVALS:	From	27 ft.	to	29		From	ft. to	ft.
	*		From	ft.	to		ft.	From	ft. to	Ft.
SA	ND PACK INT	ERVALS:	From	20 ft.	to	29	ft.	From	ft. to	Ft.
			From		to			From		Ft.
6										
GROUT	MATERIAL:	1 Neat of	cement 2	Cement grout			itonite	4 Other		
Grout Inten	vals From3	0	ft. to 1	Ft. From2	1	Ft. to	2			1
			contamination:		!-			estock pens	14 Aband	ft. toft.
	ptic tank		4 Lateral lines	7	Pit privy			l storage		I/ Gas well
	werlines		5 Cess pool		Sewage la	agoon		tilizer storage		(specify below)
	atertight sewer	lines	6 Seepage pit		Feedyard	•		ecticide storage		aminated Site
Direction fro				5			How man	•		
FROM	то	CODE	LITHOLO	OGIC LOG		FROM	то		JGGING INTE	RVALS
0	.5	Ce	ment, fill							
.5	7	Sil	ty Clay, mois	t						
7	15		ayey Sand							
15	30		nd, wet							
30	TD	En	d of Borehole			1				
7 CONTR	ACTOR'S OP			N' This water	wallwas	(x) constrain	ted (2) re-	operation or (2) -	unged upder -	ny jurisdiction and w
			10/14		well was					
	on (mo/day/yr) Contractor's L			585				true to the best of m		
	usiness name		Associate		montal			Record was complete By (signature) Da		
							as Departme	By (signature) Date of Health and Envir	onment. Bureau	of Water. Topeka.
Kansas	66620-0001.	Telephone: 913	3-296-5545. Send or	e to WATER W	ELL OWN	ER and retain	n one for you	r records.		