## GSI Job No. 027280

	WATER WELL RECORD Form	WWC-5 KSA 82a-12	12 ID No	
1 LOCATION OF WATER WE		Section Number	Township Number	Range Number
County: Reno	SE ½ SE ½ NE	1/4 22	<u>т 23 s</u>	R 06 W
Distance and direction from nea West side of Val	arest town or city street address of well if located with Iley Pride Road, between 6 <sup>th</sup> Avenue & Ri	nin city? ailroad tracks to the	e north	
2 WATER WELL OWNER:	Reno County			
RR#, St. Address, Box # :	206 W. 1 <sup>st</sup> Street		Board of Agriculture, Div	ision of Water Resources
City, State, ZIP Code :	Hutchinson, Kansas 67501		Application Number:	
3 LOCATE WELL'S LOCATO 3 AN "X" IN SECTION BOX:	N WITH 4 DEPTH OF COMPLETED WELL	<b>45</b> <del>0</del> ELEV		
AN X IN SECTION BOX:	Depth(s) Groundwater Encountered 1	19 ft.	2 ft.	3 ft. /yr
	WELL'S STATIC WATER LEVEL			/vr
	Pump test data: Well water w			
NW NE				
w w	Est. Yield gpm: Well water w	μας Λ <b>Γ</b>		
	X E Bore Hole Diameter 8.5 in. to WELL WATER TO BE USED AS: 5 Pub	lic water supply	R. and I	1. to tt.
		ield water supply	9 Dewstering	2 Other (Specify below)
SW SE				
↓ ↓ ↓ ↓ ↓	2 Irrigation 4 Industrial 7 Law			
S S	Was a chemical/bacteriological sample sub submitted		res No X If yes er Well Disinfected? Yes	
5 TYPE OF BLANK CASING			CASING JOINTS: Glue	
	RMP (SR) 6 Asbestos-Cement			
المسطاب فيبنى بنقطه بالكلاك فباليون وتبقيتهم المتقاطك تفتد				aded Flush
Blank casing diameter	2 in. to 43 ft., Dia ce Flushmount in., weight 0.	in. to	ft., Dia	in. toft.
Casing height above land surfa	ce Flushmount in., weight 0.	703 lbs./ft.	Wall thickness or gauge No	Sch. 40
TYPE OF SCREEN OR PERFO			10 Asbestos-cem	
1 Steel 3	Stainless steel 5 Fiberglass	8 RMP (SR)	11 Other (specify)	
	Galvanized steel 6 Concrete tile	9 ABS	12 None used (op 8 Saw cut	en hole)
SCREEN OR PERFORATION			8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot 6 Wire wr		9 Drilled holes	
2 Louvered shutter		ut	10 Other (specify)	
SCREEN-PERFORATED INTE	RVALS: From <b>43</b> 39.5	<b>45</b> ft. Fi	romft.	toft.
	From ft. to	ft. Fr	rom ft.	to ft.
GRAVEL PACK INTER	RVALS: From <b>42</b> ft. to	45 ft. Fi	romft.	to ft.
	From ft. to		rom ft.	to ft.
6 GROUT MATERIAL:	1 Neat cement 2 Cement grout		4 Other Bentonite G	rout
	1 ft. to 40 ft. From 40			
What is the nearest source of p				andoned water well
	4 Lateral lines 7 Pit privy			i well/ Gas well
2 Sewer lines	5 Cess pool 8 Sewage la			ther (specify below)
3 Watertight sewer lines		•	icide storage	
Direction from well?		How many	• • • • • • • • • • • • • • • • • • • •	
	DE LITHOLOGIC LOG	FROM TO	PLUGGING	NTERVALS
0 4.5	Silty Clay, dark brown			
4.5 8.5	Sitly Clay, light brown			
8.5 12	Sandy Clay, red brown			
	Sand, rusty, fine to med.			
12 15	grained			
	Sand, fine to med. grained,			
15 35	brown			
35 45	Gravel, med to coarse	· · · · · · · · · · · · · · · · · · ·	·····	
			Don Taylor was con 12-07-04 regarding	
			nate at a (0) strengt	
<b>⊢</b> J	DOWNER'S CERTIFICATION: This water well was			
completed on (mo/day/yr)			ue to the best of my knowle	
Water Well Contractor's Licens		/	cord was sompleted on (m	orday (r) 12-10-04
under the business name of	Geotechnical Services, Inc.	by (signature)	Mun HA	the
Jackson St., Ste. 420, Tope	fill in blanks and circle the correct answers. Send three co eka, Kansas 66612-1367. Telephone: 913-296-5545. Se	opies to Kansas Departmer	t of riealth and Environment, DWNER and retain one for you	bureau of water, 1000 S W ur records.

Form provided by Forms-On-A-Disk, Inc. · Dallas, Texas · (214) 340-9429

AS-12