	WATER WELL RECORD Form	n WWC-5 KSA 8	32a-1212 ID No	
1 LOCATION OF WATER WELL:		Section Num		Range Number
County: Reno	NE ½ SE ½ NE	½ 22	T 23 S	R 06 W
Distance and direction from nearest too West side of Valley Pr	wn or city street address of well if located wit ride Road, between 6 th Avenue & R	thin city? Lailroad tracks t	to the north	
2 WATER WELL OWNER:	Reno County			
RR#, St. Address, Box # :	206 W. 1 st Street		Board of Agriculture, Di	vision of Water Resources
City, State, ZIP Code :	Hutchinson, Kansas 67501		Application Number:	
3 LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	20 ft. f		
N	Depth(s) Groundwater Encountered 1			
A	WELL'S STATIC WATER LEVEL			//vr
			ft. after hours	numping
NWNE X	Est. Yield gpm: Well water v			
₩ W E	Para Usla Diameter 9 5 in to	^{vas}	. It. alter	pumpinggpm
ž W	WELL WATER TO BE USED AS: 5 Put	hlic water supply	8 Air conditioning	in. to ft.
	Bore Hole Diameter 8.5 in. to WELL WATER TO BE USED AS: 5 Put 1 Domestic 3 Feed lot 6 Oil	field water supply	9 Dewatering	12 Other (Specify below)
SWSE	2 Irrigation 4 Industrial 7 Lav	wn and garden (dom	nestic) 10 Monitoring well	SVE
* <u> </u>				
S	Was a chemical/bacteriological sample su	bilitied to Departm		
5 TYPE OF BLANK CASING LICES	submitted	0.0000000000000000000000000000000000000	Water Well Disinfected? Yes	
5 TYPE OF BLANK CASING USED:	•		CASING JOINTS: Glu	
1 Steel 3 RMP		9 Other (specify	· · · · · · · · · · · · · · · · · · ·	
2 PVC 4 ABS				aded Flush
Blank casing diameter 2	in. to 15 ft., Día Flushmount in., weight 0.	in. to	ft., Dia	in. toft.
Casing height above land surface	lushmount in., weight 0.	.703 lb:	s./ft. Wall thickness or gauge No	Sch. 40
TYPE OF SCREEN OR PERFORATION	ON MATERIAL:	7 PVC	10 Asbestos-cem	ent
1 Steel 3 Stainl	less steel 5 Fiberglass	8 RMP (S	SR) 11 Other (specify)
				pen hole)
SCREEN OR PERFORATION OPENIT		9 ABS d wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot 3	Mill slot 6 Wire wr	rapped	9 Drilled holes	
2 Louvered shutter 4	Key punched 7 Torch c		10 Other (specify)	
SCREEN-PERFORATED INTERVALS	6: From 15 ft. to	20	ft. From ft.	to ft.
	From ft. to			
GRAVEL PACK INTERVALS:	4.6	20	ft. From ft.	to ft.
	From ft. to			to ft.
6 GROUT MATERIAL: 1 Neat	cement 2 Cement grout		4 Other	
		5 Bertonite	4 Sulei	
	ft. to 13 ft. From			
What is the nearest source of possible	4 Lateral lines 7 Pit privy			bandoned water well
1 Septic tank 2 Sewer lines			•	il well/ Gas well
	5 Cess pool 8 Sewage la 6 Seepage pit 9 Feedyard	-	-	ther (specify below)
3 Watertight sewer lines	6 Seepage pit 9 Feedyard		Insecticide storage	
Direction from well? FROM TO CODE	LITHOLOGIC LOG	FROM TO	nany feet? PLUGGING	INTERVALS
	op Soil	1110111	, I LOGGING	
	lay, hard, silty, brown			
11 16 C	lay, tan, soft, sandy			
S	and, very fine to coarse grain,			
	usty			
		 		
				
			Don Taylor was as	nto stad on
			Don Taylor was co 12-07-04 regarding	
			12-01-04 regarding	ting late ioiii
		 		
7 CONTRACTOR'S OR LANDOWNE	ER'S CERTIFICATION: This water well was	(1) constructed (2	2) reconstructed, or (3) plugged ur	oder my jurisdiction and was
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr) 12-15-02 and this record is true to the best of my knowledge and belief. Kansas				
Water Well Contractor's License No.	531			lo/day/yr) //12-10-04
under the business name of	Geotechnical Services, Inc. nks and circle the correct answers. Send three corrects	by (signature)		Burgar of Water 1000 C M
	sas 66612-1367. Telephone: 913-296-5545. Se			