LOCATION OF WATER WELL: Fraction Section Number Range Numb	or
uunty: Reno SE ½ SE ½ NE ½ 22 T 23 S R 06	w W
stance and direction from nearest town or city street address of well if located within city?	
West side of Valley Pride Road, between 6 th Avenue & Railroad tracks to the north	
WATER WELL OWNER: Reno County	
R#, St. Address, Box # : 206 W. 1 st Street Board of Agriculture, Division of Water Reso	ources
ity, State, ZIP Code : Hutchinson, Kansas 67501 Application Number:	
LOCATE WELL'S LOCATON WITH 4 DEPTH OF COMPLETED WELL 39 ft. ELEVATION:	
AN "X" IN SECTION BOX: N Depth(s) Groundwater Encountered 1 1 8 ft. 2 ft. 3	
WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr	
NWNE Pump test data: Well water wasft. afterhours pumping	
Est. Yield gpm: Well water was ft. after hours pumping W X E Bore Hole Diameter 8.5 in. to 39.5 ft. and in. to	gpm
W K E Bore Hole Diameter 8.5 in. to 39.5 ft. and in. to WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well	т.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well SWSE 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify because)	elow)
2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Air Sparge	,
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample	
S submitted Vide a chemical backhological sample submitted to Department ros more submitted vide	, was
TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clampe	d
<u>1 Steel</u> 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded	u
	h
2 PVC 4 ABS 7 Fiberglass Threaded Flus	
Blank casing diameter 2 in. to 37 ft., Dia in. to ft., Dia in. to in. to	ft.
Casing height above land surface Flushmount in., weight 0.703 lbs./ft. Wall thickness or gauge No. Sch. 44	0
YPE OF SCREEN OR PERFORATION MATERIAL: <u>7 PVC</u> 10 Asbestos-cement	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)	
	iole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 37 39.5 39 ft. From ft. to	
From ft. to ft. From ft. to	^{ft.}
GRAVEL PACK INTERVALS: From 36 ft. to 39 ft. From ft. to	
From ft. to ft. From ft. to	ft.
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Bentonite Grout	
Grout Intervals From 1 ft. to 34 ft. From 34 ft. to 36 ft. From ft. to	ft .
Vhat is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water we	
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below))
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage	
Direction from well? How many feet? FROM TO CODE LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	
0 6 Lean Clay, dark brown	
6 11 Lean Clay, red brown	
11 13 Sandy Clay, red brown	
Sand, brown, fine to med	
13 30 grained	
Sand, brown, med to coarse	
27 39.5 grained	
I Don Taylor was contacted on	
Don Taylor was contacted on 12-07-04 regarding this late form	
	and was
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction a	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction a completed on (mo/day/yr) 12-15-02 and this record is true to the best of my knowledge and belief. Ka	ansas
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction a	ansas

GSI Job No. 027280

AS-2