

1 LOCATION OF WATER WELL:		Fraction	Township Number	Range Number
County: Reno		SE ¼ SW ¼ SW ¼	11 T 23 S	R 6 E W
Distance and direction from nearest town or city street address of well if located within city? 1200 W. 4th Ave., Hutchinson				
2 WATER WELL OWNER: Farmer's Cooperative Elevator RR#, St. Address, Box # : P.O. Box 6 City, State, ZIP Code : Nickerson, KS 67561		Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL 15 ft. ELEVATION: Depth(s) Groundwater Encountered 1.....ft. 2.....ft. 3.....ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was NA ft. after hours pumping gpm Est. Yield ..NA..gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter8....in. to15...ft., and.....in. to.....ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No✓..... If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No ✓		
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)		CASING JOINTS: Glued Clamped Blank casing diameter2....in. to5....ft., Diain. to.....ft., Diain. to.....ft. Casing height above land surface0....in., weightlbs./ft. Wall thickness or gauge No. Sch. 40 TYPE OF SCREEN OR PERFORATION MATERIAL 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From5....ft. to15....ft., Fromft. toft. GRAVEL PACK INTERVALS: From4....ft. to15....ft., Fromft. toft.		
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From0....ft. to1....ft., From1....ft. to4....ft., Fromft. toft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Former USTs Direction from well?				
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS				
0	1	Gravel, sand, clay,		
1	5	Sand (vf-m), v. clayey, v. sl. odor, Dark Brown		
5	9.5	Sand (vf-m), subrounded, Lt. Brown		
9.5	15	Sand (vf-c), tr. f gravel, subrounded, Gray		
		MW20 , Flushmount		
		Project Name: GF - Farmers Coop - Hutchinson		
		GeoCore # 857 , KDHE # U2 078 01317		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/2/2005 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 3/11/2005 under the business name of GeoCore, Inc. by (signature) Dan Kottel				

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY AND PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-298-5545. Send one to WATER WELL OWNER and retain one for your records.