

1) LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Reno		NW ¼ NE ¼ NE ¼		28		T 23 S		R 6 E/W	
Distance and direction from nearest town or city street address of well if located within city? 1910 S. Broadacres Road, Hutchinson									
2) WATER WELL OWNER: Koch Underground Storage									
RR#, St. Address, Box # : 1910 S. Broadacres Road					Board of Agriculture, Division of Water Resources				
City, State, ZIP Code : Hutchinson, KS 67501					Application Number:				
3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4) DEPTH OF COMPLETED WELL 147 ft. ELEVATION: 0						
			Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.						
			WELL'S STATIC WATER LEVEL 27.36 ft. below land surface measured on mo/day/yr 6/29/2005						
			Pump test data: Well water was NA ft. after hours pumping gpm						
			Est. Yield NA gpm: Well water was ft. after hours pumping gpm						
			Bore Hole Diameter 7 in. to 147 ft. and in. to ft.						
			WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well						
			1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)						
			2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring المراقبة						
			Was a chemical/bacteriological sample submitted to Department? Yes.....No ✓ ; If yes, mo/day/yr sample was submitted						
			Water Well Disinfected? Yes No ✓						
5) TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped									
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded									
7 Fiberglass Threaded. ✓									
Blank casing diameter 2 in. to 112 ft. Dia in. to ft. Dia in. to ft.									
Casing height above land surface 30 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40									
TYPE OF SCREEN OR PERFORATION MATERIAL									
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)									
9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 112 ft. to 147 ft. From ft. to ft.									
From ft. to ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 108.5 ft. to 147 ft. From ft. to ft.									
From ft. to ft. From ft. to ft.									
6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 0 ft. to 104 ft. From 104 ft. to 112 ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
13 Insecticide storage									
Direction from well? How many feet? 0									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 2 Topsoil, sandy									
2 10 Clay, silty, Brown									
10 70 Gravel and Sand (f-c), river rock,									
70 80 Sand (f-m), fair sorting,									
80 90 Sand (f-m), fair sorting, tr. green shale,									
90 100 Gravel and Sand (m-c), poor sorting									
100 122 Gravel and Sand (m-c), poor sorting,									
122 147 Shale, hard, some sand cavings, Red, some Gr									
MW15D, Abovegrade									
Project Name: GeoStat - Koch - Hutchinson									
GeoCore # 1229, #									
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/20/2005 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 6-30-05									
under the business name of GeoCore, Inc. by (signature) <i>Dale Bell</i>									