CORRECTION TO WATER WELL RECORD (WWC-5)

The following correction(s) was made to the attached WWC-5 log, in order to file the item or to rectify lacking or incorrect information.

Fraction (1/4 1/4) Section-Township-Range changed:
listed as <u>SE SE SE 1? - 23-6</u> w
changed to SESESE 1-235-6W
Other changes: Initial statements:
Changed to:
Comments:
verification method: addies, eity map, Autolinean 1:24000
initials: date:

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726 to: Kansas Dept of Health & Environment Bureau of Water Industrial Programs, Bldg 283, Forbes Field, KS 66620

			WAT	ER WELL RECORD	Form W	WC-5 KSA 82	a-1212	PLUGGING	REPOR	₹T
		TER WELL:	Fraction			Section Number	Township N	1	Range N	lumber
County:		tram pageagt town	SE 1	4 SE 1/4 address of well if loc	SE ¼		Т 23	S I	₹6W	DECADE
		um, Hutchin	•		ated within	city r				
		NER: Rex Red								
		× # :510 E.		•			Board of A	Agriculture, Divisi	on of Wate	er Resourc
	te, ZIP Code	: Hutchin					Application			
B LOCA	TE WELL'S L " IN SECTIO			COMPLETED WELL						
- 1		1		dwater Encountered C WATER LEVEL						
	i,	1		np test data: Well w					•	
	WW			gpm; Well w					_	
w	i	1 E	Bore Hole Dian	neter			and	In. to		
Σ W	!			TO BE USED AS:		water supply	8 Air conditioning	•		
	SW	SE	1 Domestic 2 Irrigation				9 Dewatering 10 Observation w	^ ግ2 Othe INΔՐ	r (Specify FTVF	below)
	1	X V		/bacterlological samp						
ļi.	· · · · · ·		nitted	1			ater Well Disinfecte		No No	,p.0 1102 50
5 TYPE	OF BLANK	CASING USED:		5 Wrought Iron		Concrete tile		INTS: Glued	Clamp	ped
11	Steel	3 RMP (SR)		6 Asbestos-Ceme		other (specify belo		Welded		
	PVC	4 ABS								
Casing h	sing diameter leight above l	and surface 60 ^{ft.ll}	below	ft., Dia in., weight		n. 10	/ft Wall thickness	or gauge No)	r
! }		R PERFORATION		worgin		7 PVC		pestos-cement		
1 S	Steel	3 Stainless	steel	5 Fiberglass		8 RMP (SR)	[11 Oth	er (specify) .]	N/A	
	Bras s	4 Galvanized		6 Concrete tile		9 ABS		ne used (open he	ole)	
0		RATION OPENING			suzed wrapp		8 Saw cut	11	None (ope	n hole)
{	Continuous sk Couvered shut		siot punched		ire wrapped irch cut		9 Drilled holes 10 Other (specif	۸		
11		ED INTERVALS:	From	/A ft. to			m m	ft. to		
			From	ft. to		ft., Fro	om	ft. to		
	GRAVEL PA	CK INTERVALS:	From	/.A tt. to	-	•		ft. to		t
1			From		**-	ft., Fro				
6 GROU	JT MATERIAL	.: 1 Neat ce	ment to 5'4"	2 Cement grout	~~ <u>3</u>	Bentonite 4	Other			
		ource of possible o					stock pens	14 Aband		
1 5	Septic tank	4 Lateral	lines	7 Pit privy		11 Fuel	storage	15 Oil we	I/Gas well	1
11	Sewer lines	5 Cess p		8 Sewage		n 12 Fertilizer storage **16 Other (specif				elow)
11	-	ver lines 6 Seepag	ge pit	9 Feedyard	ı	13 Insec	cticide storage	HOUSE	• • • • • • •	• • • • • • •
FROM	from well?	UKIH	LITHOLOGIC	CLOG	FRO	How ma	any feet?	LITHOLOGIC LO	OG.	
24 '	5'4"	Bentonite								
5'4"	5'	Cement								
5'	0	Basement					···			
i}										
:		ļ		4			D		\ //-	
							17		VL	U
<u> </u>										
								Fun + n	1998	
	-							JUL 1 0	1770	
							DUC	\ <u></u>		
							801	REAU OF	WAT	ER
-	1	<u> </u>								
7 CONT	TRACTOR'S	OR LANDOWNER'S	S CERTIFICA	TION: This water wel	l was pipipor	STANDSHIP COLORESTON FOR STANDSFOR	अंगलकाम्बलम्	olugged under m	y jurisdicti	on and wa
				This Wate					ige and be	elief. Kansa
				& PEST CONTR				1 '// 4 '	1 Well	s
INSTRU	CTIONS: Use	typewriter or ball po	oint pen, <i>PLEA</i>	SE PRESS FIRMLY	and PRINT	clearly. Please fill	In blanks, underline	or circle the corr	ect answe	ers. Send to
		Department of Hea		ment, Division of Envi	ironment, Er	vironmental Geolo	gy Section, Topeka	, KS 66620. Serv	one to W	ATER WEI