

CORRECTED

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number			
County: Reno		SW ¼ SW ¼ SW ¼		28		T 23 S		R 6 E/W			
Distance and direction from nearest town or city street address of well if located within city? 1910 S. Broadacres Road, Hutchinson											
2 WATER WELL OWNER: Koch Underground Storage											
RR#, St. Address, Box # : 1910 S. Broadacres Road					Board of Agriculture, Division of Water Resources						
City, State, ZIP Code : Hutchinson, KS 67501					Application Number:						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL 100 ft. ELEVATION: 0								
			Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.								
			WELL'S STATIC WATER LEVEL 26 ft. below land surface measured on mo/day/yr 9/27/2005								
			Pump test data: Well water was NA ft. after hours pumping gpm								
			Est. Yield NA gpm: Well water was ft. after hours pumping gpm								
			Bore Hole Diameter 8 in. to 100 ft., and in. to ft.								
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well											
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)											
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well											
Was a chemical/bacteriological sample submitted to Department? Yes.....No✓; If yes, mo/day/yr sample was submitted											
Water Well Disinfected? Yes No ✓											
5 TYPE OF BLANK CASING USED:											
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped											
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded											
7 Fiberglass Threaded. ✓											
Blank casing diameter 2 in. to 90 ft., Dia in. to ft., Dia in. to ft.											
Casing height above land surface 24 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40											
TYPE OF SCREEN OR PERFORATION MATERIAL											
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement											
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)											
12 None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)											
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes											
7 Torch cut 10 Other (specify)											
SCREEN-PERFORATED INTERVALS: From 90 ft. to 100 ft., From ft. to ft.											
From ft. to ft., From ft. to ft.											
GRAVEL PACK INTERVALS: From 86 ft. to 100 ft., From ft. to ft.											
From ft. to ft., From ft. to ft.											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other											
Grout Intervals: From 0 ft. to 1.5 ft., From 1.5 ft. to 86 ft., From ft. to ft.											
What is the nearest source of possible contamination:											
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well											
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well											
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)											
13 Insecticide storage											
Direction from well? How many feet? 0											
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
0		5				79		100		Sand (f-c), Tan/Black	
5		10		Silt/clay, sl. firm, Brown/Reddish Brown							
10		14.5		Clay, sl. firm, Light Brown							
14.5		19.5		Clay/silt, sl. firm, tr. vf sand, Light Brown							
19.5		24		Silt, clayey, sl. firm, tr. vf sand, Gray							
24		29		Clay/silt, sl. firm-sl. soft, Gray/Lt. Brown							
29		31		Sand (vf-m, little coarse), clayey lenses, Lt. Gr							
31		34		Sand (vf-m), silty, Light Gray							
34		39		Sand (f-c), poorly sorted, clean, Tan							
39		44		Sand (f-c), tr. fine gravel, Tan/Black							
44		50		Sand (m-c), little fine gravel, Brown/Tan							
50		54		Sand (f-c), less gravel, Tan/Brown							
54		69		Sand (vf-c), Tan/Brown						MW44, Abovegrade	
69		74		Sand (f-m, some coarse), Tan/Brown						Project Name: Arcadis - Oxy - Hutch	
74		79		Sand (f-m), Tan/Brown						GeoCore # 1235, #	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/15/2005 and this record is true to the best of my knowledge and belief.											
Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 10/10/2005											
under the business name of GeoCore, Inc. by (signature) <i>Daa Rll</i>											

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.