

1 LOCATION OF WATER WELL:		Fraction		Section Number	Township Number	Range Number
County: Reno		NW ¼ NW ¼ NE ¼		1	T 23 S	R 6 E/W
Distance and direction from nearest town or city street address of well if located within city? 25 E. 30th St., Hutchinson						
2 WATER WELL OWNER: Mark Coberly						
RR#, St. Address, Box # : 4003 E. 23rd Street				Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Hutchinson, Kansas 67502				Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 32 ft. ELEVATION:				
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.				
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr				
		Pump test data: Well water was NA ft. after hours pumping gpm				
		Est. Yield NA gpm: Well water was ft. after hours pumping gpm				
		Bore Hole Diameter 8 in. to 32 ft. and in. to ft.				
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well						
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)						
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Air sparge						
Was a chemical/bacteriological sample submitted to Department? Yes.....No ☒ ; If yes, mo/day/yr sample was submitted						
Water Well Disinfected? Yes No ☒						
5 TYPE OF BLANK CASING USED:						
1 Steel		3 RMP (SR)		5 Wrought iron		8 Concrete tile
2 PVC		4 ABS		6 Asbestos-Cement		9 Other (specify below)
Blank casing diameter 2 in. to 30 ft. Dia		7 Fiberglass		CASING JOINTS: Glued		Clamped
Casing height above land surface 0 in., weight		lbs./ft. Wall thickness or gauge No. Sch. 40		Welded		Threaded ☒
TYPE OF SCREEN OR PERFORATION MATERIAL						
1 Steel		3 Stainless steel		5 Fiberglass		7 PVC
2 Brass		4 Galvanized steel		6 Concrete tile		8 RMP (SR)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		8 Saw cut		11 None (open hole)
1 Continuous slot		3 Mill slot		9 Drilled holes		10 Asbestos-cement
2 Louvered shutter		4 Key punched		7 Torch cut		12 None used (open hole)
SCREEN-PERFORATED INTERVALS:		From 30 ft. to 32 ft.		From ft. to ft.		From ft. to ft.
GRAVEL PACK INTERVALS:		From 28 ft. to 32 ft.		From ft. to ft.		From ft. to ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete						
Grout Intervals: From 0 ft. to 2 ft. From 2 ft. to 28 ft. From ft. to ft.						
What is the nearest source of possible contamination:						
1 Septic tank		4 Lateral lines		7 Pit privy		10 Livestock pens
2 Sewer lines		5 Cess pool		8 Sewage lagoon		11 Fuel storage
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		12 Fertilizer storage
Direction from well?		How many feet?		13 Insecticide storage		14 Abandoned water well
						15 Oil well/Gas well
						16 Other (specify below)
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS						
0	0.5	Concrete,				
0.5	1	Sand (fill),				
1	2.5	Silt, sl. moist, v. sl. odor, Gray				
2.5	4	Clay, v. silty, moist, plastic, no odor, Brown				
4	8	Clay, v. sl. silty, moist, stiff, no odor, Brown				
8	8.5	Sand (vf-m), v. silty, moist, Brown				
8.5	11.5	Clay, silty, sandy, moist, no odor, Dark Brown				
11.5	14.5	Sand (vf-m), silty, sl. old gas odor, Gray to Gr				
14.5	20	Sand (vf-c), silty, saturated, Dark Gray				
20	28	Sand (f-c) w/f gravel, subrounded, saturated,				
28	32	Sand (f-c) w/f-m gravel, subrounded, Brown				
AS3, Tag # 00371580, Flushmount						
Project Name: GF - Danny's Service						
GeoCore # 1282, KDHE # U2 078 00856						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/26/2006 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 5/19/2006						
under the business name of GeoCore, Inc. by (signature) <i>Dan Roll</i>						