WA	TER WELL RE	ECORD	Form WWC	-5	Division of Wate	r Resources; App. No.		
	LOCATION OF W		Fraction	5/3	Section Number			
	County: Reno		SE1/4 SE 1/4 S		8	т 23 s	R 6 E/W	
		on from nearest town or ci			T 12 1	•	egrees, min. of 4 digits)	
located within city? 4702 W, 44h He			utchinson, Ks.					
2	WATER WELL O	WNER: Troy Glass	1		Elevation:			
	RR#, St. Address, B	Box# : Iroy blast	tón		Datum:			
	City, State, ZIP Cod	le : 4702 W. 4	th In, Ks 67501		Data Collection	Method:		
3	LOCATE WELL'S	4 DEPTH OF COM	PLETED WELL	30	ft.			
	LOCATION							
	WITH AN "X" IN Depth(s) Groundwater Encountered (1)							
	SECTION BOX: WELL'S STATIC WATER LEVEL							
	N	gpm						
		WELL WATER TO B	gpm: Well water wasft. after					
w	NW NE	NW RE RE E WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Inje 11 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Oth						
W		2 Irrigation 4 Ind	lustrial 7 Domest	ic (lawn	& garden) 10 Mor	nitoring well .	STOCK	
	CW CF							
	was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yrs							
	Sample was submitted							
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: GluedX Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded								
5	1 Steel 2 PM	USED: 5 Wrought	Iron 8 Con					
	2 P <u>VC.</u> 4 AF	SS _ 7 Fiberglass	-Cement 9 Othe	er (specify	y below)	Thread	ed	
Bla	ank casing diameter.	5 in. to3	ft Diameter		in. to ft	Diameter	in. toft.	
Blank casing diameter 5 in to 20 ft., Diameter in to ft., Diameter in to ft. Casing height above land surface 40 in., Weight 160 lbs./ft. Wall thickness or guage No. 214								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)								
2 Brass 4 Galvanized Steal 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:								
1 Continuous slot 3 Mill slot 5 Guazed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)								
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
From								
GRAVEL PACK INTERVALS: From								
From								
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Hole Plug. Grout Intervals: From 19 ft. to ft., From ft. to ft., From ft. to ft.								
Grout Intervals: From								
What is the nearest source of possible contamination:								
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well below)								
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well								
Direction from well?								
FR	OM TO	LITHOLOGIC	CLOG	FRON	И ТО	PLUGGING IN	TERVALS	
	0 3 T	Sp Soil						
	$\frac{2}{2}$	rown Clay						
-	6 30 M	edium Sánd		-				
_								
							1111	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged								
under my jurisdiction and was completed on (mo/day/year) /2-26 and this record is true to the best of my knowledge and belief. We have a word was completed on (mo/day/year) /2-31-21-21-21-21-21-21-21-21-21-21-21-21-21								
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 10-31-06 under the business name of Assacrate Burns Eat. by (signature) by (signature)								
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks, underline or circle the correct answers. Send top								
three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone								
/8:	785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at							

http://www.kdhe.state.ks.us/geo/waterwells.