WATER WELL RECORD Form WWC-5	Division of Water Resources; App. No.
1 LOCATION OF WATER WELL: Fraction	Section Number   Township Number   Range Number
County: Reno   SW ½ SE ½ SE	14 25 T 23 S R 6 W
located within city? 800 Wilbeck Drive, South Hutchinson, KS	Latitude: N 38.01410°
•	Longitude: W 97.92610°
2 WATER WELL OWNER: Pepsi Cola Warehouse	Elevation: RIM: 1524.63 TOC: 1524.33
RR#, St. Address, Box # : 101 W 48th St	Datum: above mean sea level
City, State, ZIP Code : Wichita KS 67217-4937	Data Collection Method: legal survey
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL _	18.0 ft.
LOCATON	MW2R
WITH AN "X" IN Depth(s) Groundwater Encountered 1	ft. 2 ft. 3 ft. 50 ft. below land surface measured on mo/day/yr 6/1/09
SECTION BOX: WELL'S STATIC WATER LEVEL 10.	the below land surface measured on mo/day/yr 6/1/09
N Pump test data: Well water was	ft. after hours pumping gpm
Est. Yield gpm: Well water was	ft. after hours pumping gpm
	lic water supply 8 Air conditioning 11 Injection well supply 9 Dewatering 12 Other (Specify below)
W E 1 Domestic 3 Feed for 6 On field water 2 Irrigation 4 Industrial 7 Domestic (law	m & garden) (1) Monitoring well
	n a garden) to internity wen
SW SE Was a chemical/bacteriological sample sub	mitted to Department? Yes No X; If yes, mo/day/yrs
S Sample was submitted	Water Well Disinfected? Yes No X
5 TYPE OF CASING USED: 5 Wrought Iron 8 C	oncrete tile CASING IOINTS: Glued Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 C	ther (specify below) Welded
(2) PVC 4 ABS 7 Fiberglass	Threaded Y
PVC 4 ABS 7 Fiberglass Blank casing diameter 2 in. to 8 ft., Dia Casing height below land surface 0.30 ft., Weight	in to ft Dia in to ft
Casing height helow land surface 0.30 ft Weight	lbs /ft Wall thickness or gauge No.
TYPE OF SCREEN OR PERFORATION MATERIAL:	100316 Wan districted of Bange XVII
1 Steel 3 Stainless steel 5 Fiberglass (7) PVC	9 ABS 11 Other (specify)
1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR)	10 Asbestos-Cement 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	Torch cut 9 Drilled holes 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 8	Saw Cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 8 ft.	to 18 ft. From ft. to ft.
From ft.	to ft. From ft. to ft.
GRAVEL PACK INTERVALS: From 6 ft.	to 18 ft. From ft. to ft.
1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 SCREEN-PERFORATED INTERVALS: From 8 ft.  GRAVEL PACK INTERVALS: From 6 ft.  From ft.	to ft. From ft. to ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout (3	Bentonite (4) Other Concrete: 0-2 ft.
Grout Intervals From 2 ft. to 6 ft. From	ft. to ft. From ft. to ft.
What is the nearest source of possible contamination:	
	ivestock pens 13 Insecticide Storage 16 Other (specify
2 Sewer lines 5 Cess pool 8 Sewage lagoon (11) F	
	ertilizer storage 15 Oil well/ gas well
	many feet? ~73
	ROM TO PLUGGING INTERVALS
0 1 Gravel with sand and brown silt	
1 15 Sand, red brown, medium grained, not well sorted 15 18 Sand, red brown, fine to coarse grained	
15 16 Sand, red brown, the to coarse gramed	
	Flushmount waiver from BOW
	FIGSHINGUIT WAIVEL HOIL DOW
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:	This water well was (1) constructed, (2) reconstructed, or (3) plugged
under my jurisdiction and was completed on (mo/day/year) 6/1/09	and this record is true to the best of my knowledge and belief.
Kansas Water Well Contractor's License No. 757 . This Water V	Vell Record was completed on mo/day/year) 6/11/09
	(signature)
INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Tele	copies to Kansas Department of Health and Environment, Bureau of Water, shone 785-296-5522. Send one to WATER WELL OWNER and retain one for
your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.	