WATE	R WELI	REC	CORD	Form WV	VC-5	Division of Water Resources; App. No.				
1	_		TER WELL:		Carr	Section Numb	er Tov	wnship Number	Range Number	
Coun	ty: K	eno	<i>C</i>	NE1/4 SE1/		25 Clabal Baritian		23 S	R 6 E/W	
Distance and direction from nearest town or city street address of well if located within city?						Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude:				
locati	ed willing c	5-/	Detroit 1	n S. Hute	hincon					
2 WA	TER WEI			iel Simme		Elevation:				
1	, St. Addre		Gaor	etroit	<i>n y</i>	Datum:				
1	State, ZIP		<i>310</i>	toh, KS 673	505	Data Collecti	ion Meth	od:		
3 LOC	ATE WEI	LL'S	4 DEPTH OF CO	MPLETED WELL	40			iou.		
ł.	ATE WEI		7 DEI III OF CC	WII LETED WEEL	······ / ·· ··· ····	• • • • • • • • • • • • • • • • • • • •	11.			
	H AN "X"	'IN	Depth(s) Groundwa	ater Encountered (1)	ft. (2)		ft. (3)	ft.	
	SECTION BOX: WELL'S STATIC WATER LEVEL 1.5 ft. below land surface measured on mo/day/yr. 9-1/7-0.9									
	N Pump test data: Well water wasft. after									
			Est. Yield	gpm: Well water wa	S	ft. after		hours pumping	gpm	
NV	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well									
w	w									
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well										
SW	Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yrs									
	Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yrs									
Sample was submitted										
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped										
			JSED: 5 Wroug	ght Iron 8 C	Concrete tile	CA	SING JO	INTS: Glued	-	
				tos-Cement 9 O					 I	
QPVC 4 ABS 7 Fiberglass Threaded.										
QPVC 4 ABS 7 Fiberglass Threaded. Blank casing diameter 5 in. to 30 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 1.2 in., Weight 2.25 lbs./ft. Wall thickness or guage No. 1.6.9										
TYPE OF SCREEN OR PERFORATION MATERIAL:										
1 Steel 3 Stainless Steel 5 Fiberglass PVC 9 ABS 11 Other (Specify)										
1 Steel 3 Stainless Steel 5 Fiberglass										
SCREEN OR PERFORATION OPENINGS ARE:										
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)										
2 Louvered shutter 4 Key punched 6 Wire wrapped Saw cut 10 Other (specify)										
SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft.										
From										
GRAVEL PACK INTERVALS: From										
			110	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		10., 1 101		16. 10		
6 GRO	UT MATE			2 Cement grout	Bentonite	4 Other				
Grout In				2.2 ft., From		ft. to	ft., Fro	om	ft. toft.	
1			e of possible contami							
	Septic tank			es 7 Pit privy	10 Livest				16 Other (specify	
	Sewer lines		5 Cess pool	8 Sewage lagoon		-		oned water well	below)	
			lines 6 Seepage p					. 6		
		1?,		CICI OC	 	· · · · · · · · · · · · · · · · · · ·			EDVALC	
FROM	TO	<u></u>	LITHOLO	GIC LOG	FROM	TO	P	LUGGING INT	EKVALS	
Q	6	Br	Clay							
6	14	GH								
14	43	F				+ + -				
27	75	Ja	nd + Grave	2/						
						+				
				, , , , , , , , , , , , , , , , , , , ,		+ +				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed. (2) reconstructed or (3) plugged										
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)										
Kansas	Water Well	Contr	actor's License No.	44.7 This Wa	ater Well Red	cord was compl	leted on (mo/dav/year) . 9	-22-09	
1	e business			Drilling		y (signature)			, , , , , , , , , , , , , , , , , , ,	
INSTRUC	CTIONS: Us	e typew	riter or ball point pen. P	PLEASE PRESS EARMLY a	and PRINT clear	ly. Please fill in b	olanks, unde	erline or circle the co		
				nment, Bureau of Water, C						
785-296-5 http://wwv			to WATER WELL Co ell/index.html.	WNER and retain one	t for your re	corus. ree of	\$5.00 10	r eacn constructed	d well. Visit us at	