WATER V	WELL REC	CORD	Form W	WC-5	Division of Water		o. L	
1 LOCATION OF WATER WELL: County: Reno		Fraction NW ¼ NE ¼ SE	1/4 SW 1/4	Section Number 9	Township No. T 23 S	Range Number R 6 DE VW		
Street/Rural Address of Well Location; if unkn			f unknown, distance &	direction	Global Positioning System (GPS) information:			
from nea	from nearest town or intersection: If at owner's address, check here .					Latitude: .38,05971		
					Longitude: 097.98824 (in decimal degrees)			
2 WATER WELL OWNER: Linda Seeger					Datum: ☐ WGS 84, ☐ NAD 83, ☑ NAD 27			
		_ Linda O			Collection Method:		CSX	
RR#, Street Address, Box #: 3409 W City, State, ZIP Code : Hutching			. om son, Kansas 67501		☐ GPS unit (Make/Model: Garmin csx ☐ Digital Map/Photo, Topographic Map, ☐ Land Survey			
Tratorina			SOII, Narisas 07301		Est. Accuracy:	3 m, 🛛 3-5 m, 🗌	5-15 m, >15 m	
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 30 ft.								
SECTIO	N BOX:					ft. ((3) ft.	
-	N	WELL'S STATI	C WATER LEVEL	ter Encountered (1)				
			gpm. Well water was					
w NW	NE E	Bore Hole Diam	eter 9in. to .30ft., andin. toft.					
WELL WATER TO BE USED AS: Public water supply Geothermal Injection								
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below Irrigation Industrial Domestic-lawn & garden Monitoring well								
S If yes, mo/day/yr sample was submitted								
1 mile Water well disinfected? ✓ Yes □ No								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter .5								
Casing height above land surface. 16 in., Weight .160 lbs./ft., Wall thickness or gauge No214 lbs./ft., Wall thickness or gauge No214 lbs./ft.								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☑ PVC ☐ Other (Specify)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From								
From								
GRAVEL PACK INTERVALS: From30								
From								
Grout Intervals: From .15 ft. to .0 ft., From ft. to ft. to ft. to ft.								
What is the nearest source of possible contamination:								
✓ Septic tank								
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well								
	n from well .E.			, , , , , , , , , , , , , , , , , , , 				
FROM 1 0 2	Top so	LITHOLOG	IC LUG	FROM	TO LITHO. LO	(cont.) or PLU	JGGING INTERVALS	
2 6	Brown					to Contribution of the contribution and a security to security of the contribution of		
6 30		and & gravel						
						to a service and the service a		

			nit Marani i anno an bhann ann ann an an an an an an an an an a			***************************************		
			the complete the thirt content of the content of th					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .8-4-10								
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 8-6-10								
under the business name of Rosencrantz Bemis Ent. by (signature) Likes Dados D								
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212 Check: ✓ White Copy, ☐ Blue Copy, ☐ Pink Copy								