WATER WELL	RECORD	Form W	WC-5	Division of Wa	ter Resources App. N	o. L	
1 LOCATION OF WATER WELL:		Fraction		Section Number			
County: Reno		SW 1/4 SE 1/4 NE	1/4 NE 1/4			R 6 □E ☑W	
	ress of Well Location: i			Global Positioning System (GPS) information:			
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here							
Hom hearest town	n of intersection. If at C	wher s address, theth	Latitude: 38.06807 (in decimal degrees)				
				Longitude: 097.94246 (in decimal degrees)			
				Elevation: 6525			
2 WATER WELL OWNER: Nancy Meyers				<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ② NAD 27			
1			Collection Method	Comin			
RR#, Street Address, Box #: 615 West 14th. Street				GPS unit (Make/Model: Garmin)			
City, State, ZIP (Code : Hutchins	son, Kansas 67502		Digital Map/Photo, Topographic Map, Land Survey			
				Est. Accuracy:	<3 m, 🖊 3-5 m, 🔲	5-15 m, >15 m	
3 LOCATE WELL							
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 42							
SECTION BOX:							
N	N WELL'S STATIC WATER LEVEL. 12 ft. below land surface measured on mo/day/yr. 5-17-2012						
Pump test data: Well water was							
LECT VIELD W-11 A.A. 1							
W NW NE -	1 1 2 2 2 2 2 2	eter 10 in to	f	end ir	to	A	
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							
SWSE							
☐ Irrigation ☐ Industrial ☑ Domestic-lawn & garden ☐ Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes No							
S	If yes, mo/o	lay/yr sample was sub	mitted	•••••			
mile Water well disinfected?							
5 TYPE OF CASING USED: Steel V PVC Other							
CASING JOINTS: ☑ Glued ☐ Clamped ☐ Welded ☐ Threaded							
Casing diameter .5. in. to .32. ft., Diameter in. to ft., Diameter in. to ft.							
Casing height above land surface 14 in., Weight 160 lbs/ft., Wall thickness or gauge No214							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
Steel Stainless Steel ✓ PVC Other (Specify)							
Brass Galvanized Steel None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)							
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)							
SCREEN-PERFORATED INTERVALS: From 32. ft. to 42. ft., From ft. to ft.							
From							
GRAVEL PACK INTERVALS: From 42 ft. to .15 ft., From ft. to ft.							
From							
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other							
Grout Intervals: From 15 ft. to 0 ft., From ft. to ft. ft. ft.							
What is the nearest source of possible contamination:							
Distriction Community West							
FROM TO	LITHOLOG	C TOG	FROM	TO LITHO. L	.UG (cont.) <u>or</u> PLU	GGING INTERVALS	
	p soil						
3 8 Br	own clay						
	edium sand and grave	<u> </u>					
					· · · · · · · · · · · · · · · · · · ·		
			 				
 							
	····		ļ				
 							
 			 -				
7.CONTRA 0707	COBIANDO	CODDITION TO	N. 171-1-				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed, reconstructed, or plugged							
under my jurisdiction and was completed on (mo/day/year) 5-17-2012 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 5-22-2012							
under the business name of Rosencrantz-Bernis Enterprise by (signature)							
INSTRUCTIONS: Use ty pewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies							
(white, blue, pink) to Kar	nsas Depar tment of Health a	nd E nvironment, Bureau o	of Water, Geolog	gy Section, 1000 SW J	ackson St., Suite 420,	Topeka, Kansas 666 12-1367.	
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at							
http://www.kdheks.gov/waterwell/index.html.							
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy							