WATER WELL RECORD FOrm WWC-5 Division of Water Resources App. No.						
1 LOCATION OF WATER WELL: County: Reno			Fraction NW 1/4 NE 1/4 NW 1/4 SW	Section Number Township No. Range Number T 23 S R 6 DE 7W		
Street/Rural Address of Well Location; if unknown, distance & direction						
from nearest town or intersection: If at owner's address, check here \(\mathbb{Z}\) .						
Hom	nomination town of intersection. If at owner 5 address, enter here			Longitude: 097.93661 (in decimal degrees)		
				Elevation: 1541		
				Datum: WGS 84, NAD 83, NAD 27		
2 WATER WELL OWNER: Rick Crank				Collection Method:		
RR#, Street Address, Box #: 129 East F. Street				GPS unit (Make/Model: Garmin)		
City, State, ZIP Code : South Hutchinson, Kansas 67505			lutchinson, Kansas 67505	☐ Digital Map/Photo, 【 Topographic Map, ☐ Land Survey		
				Est. Accuracy:		
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 45						
i	H AN "X FION BO					
SEC.	N N	Depth(s) Ground	C WATER LEVEL 15	ft. (2) ft. (3) ft		
[l loom rooms			ft. after hours pumping gpm		
NW NE		E EST. TIELD	EST. YIELDgpm. Well water wasft. afterhours pumpinggpm Bore Hole Diameter 10in. toft.			
w				vater supply Geothermal Injection well		
		□ □ Domostio				
sv	SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)					
	☐ Irrigation ☐ Industrial ☑ Domestic-lawn & garden ☐ Monitoring well					
	S 1 mile		day/yr sample was submitted			
Water well disinfected? ✓ Yes □ No						
5 TYPE OF CASING USED: Steel PVC Other						
CASING JOINTS: Glued Clamped Welded Threaded						
Casing diameter 5 in. to 35 ft., Diameter in. to						
Casing height above land surface. 14 in., Weight .160 lbs/ft., Wall thickness or gauge No214						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
☐ Steel ☐ Stainless Steel						
Brass Galvanized Steel None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)						
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)						
SCREEN-PERFORATED INTERVALS: From						
From						
From						
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other						
Grout Intervals: From .17 ft. to .0 ft., From ft. to ft., From ft. to ft.						
What is the nearest source of possible contamination: Septic tank						
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well						
□ Watertight sewer lines □ Seepage pit □ Feedyard □ Fertilizer storage □ Oil well/gas well Water tight sewer						
Direction from well South Distance from well 40ft.						
FROM	ТО	LITHOLOG		TO LITHO. LOG (cont.) or PLUGGING INTERVALS		
0	3	Top soil				
3	10	Brown clay				
10	45	Medium sand and grav	ol .			
, , , , , , , , , , , , , , , , , , , 	- <u>`</u> -	modium sand and grav	U1			
<u> </u>						
	<u> </u>					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed, reconstructed, or plugged						
under my jurisdiction and was completed on (mo/day/year) .5-17-2012 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 5-22-2012						
under the business name of Rosencrantz-Bemis Enterprise by (signature) Living 1987 1987 1987 1987 1987 1987 1987 1987						
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367.						
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at						
http://www.kdheks.gov/waterweil/index.html.						
KSA 82a-1212 Check: ✓ White Copy, ☐ Blue Copy, ☐ Pink Copy						