

1 LOCATION OF WATER WELL: Fraction SE 1/4 SW 1/4 SW 1/4 Section Number 1 Township Number T 23 S Range Number R 6 E
 County: Reno
 Distance and direction from nearest town or city street address of well if located within city?
1900 W Madison

2 WATER WELL OWNER: Joe McGuire
 RR#, St. Address, Box #: 1900 N. Madison
 City, State, ZIP Code: Hutchinson KS 67502
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
W	NW	NE	E
	SW	SE	
S			

4 DEPTH OF COMPLETED WELL: 32 ft. ELEVATION: 6-19-27
 Depth(s) Groundwater Encountered 1. 18 ft. 2. 18 ft. 3. 18 ft.
 WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 6-19-27
 Pump test data: Well water was 20 ft. after 3 hours pumping 25 gpm
 Est. Yield 25 gpm: Well water was 20 ft. after 3 hours pumping 25 gpm
 Bore Hole Diameter: 8 in. to 32 ft., and 32 in. to 32 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 Blank casing diameter 5 in. to 24 ft., Dia. 24 in. to 24 ft., Dia. 24 in. to 24 ft.
 Casing height above land surface 16 in., weight 160 lbs./ft. Wall thickness or gauge No. 160
 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 24 ft. to 32 ft., From 24 ft. to 32 ft., From 24 ft. to 32 ft.
 GRAVEL PACK INTERVALS: From 24 ft. to 32 ft., From 24 ft. to 32 ft., From 24 ft. to 32 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 20 ft., From 20 ft. to 32 ft., From 20 ft. to 32 ft.
 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
 Direction from well? How many feet? 60

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	18	Top Soil			
18	20	Sand			
20	32	Sand & Gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-19-27 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 440 This Water Well Record was completed on (mo/day/yr) 6-19-27 under the business name of Carl Vincent Service by (signature) Carl Vincent
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T 23

R 6

E 6

SEC. 1

1/4

1/4

1/4