

1 LOCATION OF WATER WELL: County: <u>Reno</u>		Fraction <u>S 1/4 NW 1/4 SW 1/4</u>	Section Number <u>1</u>	Township Number <u>T 23 S</u>	Range Number <u>R 6 EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>105 Hyde Park Hutchinson</u>					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: <u>35</u> ft. ELEVATION:		
			Depth(s) Groundwater Encountered <u>1</u> ft. <u>19</u> ft. 3. ft.		
			WELL'S STATIC WATER LEVEL <u>19</u> ft. below land surface measured on mo/day/yr <u>5-12-92</u>		
			Pump test data: Well water was <u>20</u> ft. after <u>1</u> hours pumping <u>50</u> gpm		
			Est. Yield <u>75</u> gpm: Well water was <u>20</u> ft. after <u>6</u> hours pumping <u>35</u> gpm		
			Bore Hole Diameter <u>9</u> in. to <u>20</u> ft. and <u>6</u> in. to <u>35</u> ft.		
WELL WATER TO BE USED AS:			5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> <u>X</u> ; If yes, mo/day/yr sample was submitted			Water Well Disinfected? Yes <u>X</u> No		
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>6</u> in. to <u>25</u> ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface <u>12</u> in. weight lbs./ft. Wall thickness or gauge No. <u>250</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>25</u> ft. to <u>35</u> ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout intervals: From <u>3</u> ft. to <u>20</u> ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? <u>West</u> How many feet? <u>15</u>					
FROM		TO		LITHOLOGIC LOG	
FROM		TO		PLUGGING INTERVALS	
0		2		Sandy Soil	
2		12		Sandy clay	
12		16		fine sand	
16		21		fine gravel	
21		35		medium gravel	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5-12-92</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>193</u> This Water Well Record was completed on (mo/day/yr) <u>6-29-92</u> under the business name of <u>Price Water Well Serv.</u> by (signature) <u>John Dawson</u>					