

MW-5

2011057

WATER WELL RECORD

Form WWC-5


KSA 82a-1212

1 LOCATION OF WATER WELL: County: RENO	Fraction NW 1/4 NW 1/4 NE 1/4	Section Number 1	Township Number T 23 S	Range Number R 6 E
--	---	----------------------------	----------------------------------	------------------------------

Distance and direction from nearest town or city street address of well if located within city?

25 E. 30th, HUTCHINSON

2 WATER WELL OWNER: Mark Coberly RR#, St. Address, Box #: 3217 E. meadow lake City, State, ZIP Code: Hutchinson, KS, 67502	Board of Agriculture, Division of Water Resources Application Number:
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 22.0 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 16.5 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 16.80 ft. below land surface measured on mo/day/yr 2-11-93 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X
--	---

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Blank casing diameter 2 in. to ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface: Flush in. weight .703 lbs./ft. Wall thickness or gauge No. .154 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 12.0 ft. to 22.0 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 11.0 ft. to 22.0 ft. From ft. to ft.	CASING JOINTS: Glued Clamped Threaded Flush
---	---

6 GROUT MATERIAL: 1 Neat cement 3 Cement grout 3 Bentonite 4 Other Grout Intervals: From 11.0 ft. to 1.0 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? SE How many feet? 280'
--

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	11.0	silt, sandy			
11.0	16.0	Sand, med. to coarse, well SORTED			
16.0	22.0	coarse sand & gravel, subangular to subrounded			
Flush mount waiver granted on 12-10-92 for Danny's OK Service; KDHE 02078856 by Don Taylor					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-11-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 2-17-93 under the business name of GSI by (signature) Allison Traven
