

CORRECTED

## WATER WELL RECORD Form WWC-5 KSA 82a-1212

LOCATION OF WATER WELL: County: Reno	Fraction NE 1/4 SE 1/4 NW 1/4	Section Number 1	Township Number T 23 S	Range Number R 6 EW
---	----------------------------------	---------------------	---------------------------	------------------------

Distance and direction from nearest town or city street address of well if located within city?

2617 N. Main, Hutchinson, Kansas


WATER WELL OWNER: T &amp; E Oil

RR#, St. Address, Box #: P.O. Box 1303

City, State, ZIP Code: Hutchinson, Ks. 67504

Board of Agriculture, Division of Water Resources

Application Number:

LOCATE WELL'S LOCATION WITH  
AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 25 ft. ELEVATION: 96.63

Depth(s) Groundwater Encountered 18 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 13.36 ft. below TOC measured on mo/day/yr 06-02-93

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 7 5/8 in. to 25 ft., and in. to

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:

1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded

Blank casing diameter 2 in. to 15 ft., Dia. in. to ft., Dia. in. to

Casing height above land surface -3 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 15 ft. to 25 ft., From ft. to

From ft. to ft., From ft. to

GRAVEL PACK INTERVALS: From 13 ft. to 25 ft., From ft. to

From ft. to ft., From ft. to

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout intervals: From 0 ft. to 11 ft., From 11 ft. to 13 ft., From ft. to

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

Direction from well? northwest How many feet? 10

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 6" CONCRETE

6" 11.5 BRN SLTY CLY Flush mount cover

11.5 17 F TO C SND MW2 #18

17 24 F TO C SND/F TO M GRVL, MOD

CONTAMINATION

RECEIVED

JAN 20 2005

BUREAU OF WATER

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was

Completed on (mo/day/year) 06-02-93 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 06-02-93

under the business name of GeoCore Services, Inc. by (signature) Dale R. R.

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.