WATER WELL RECORD Form WWC-5 KSA 82a-1212

LOCATION OF WATER WELL	Fraction	Section Number	Township Number	Range Number
County: Reno	SW ¼ SE ¼ NW ¼	1	T 23 S	R 6 E/(W)

Distance and direction from nearest town or city? | Street address of well if located within city? 503 W. 23rd Hutchinson

1 WATER WELL OWNER: CHET WATSON
RR#, St. Address, Box # : 503 W. 23rd
City, State, ZIP Code : Hutchinson Kan. 67501

Board of Agriculture, Division of Water Resources Application Number:

2 DEPTH OF COMPLETED WELL 37 ft. Bore Hole Diameter 9 in. to 21 ft., and 6 in. to 37 ft.

Well Water to be used as:
1 Domestic 3 Feedlot 5 Public water supply 6 Oil field water supply 8 Air conditioning 9 Dewatering 10 Observation well 11 Injection well 12 Other (Specify below)
2 Irrigation 4 Industrial (7) Lawn and garden only

Well's static water level 21 ft. below land surface measured on 2 month 19 day 81 year

Pump Test Data: Well water was 22 ft. after 1 hours pumping 25 gpm
Est. Yield 50 gpm: Well water was ft. after hours pumping gpm

3 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 6 Asbestos-Cement 8 Concrete tile 9 Other (specify below)
(2) PVC 4 ABS 7 Fiberglass

Casing Joints: Glued X Clamped
Welded
Threaded

Blank casing dia 6 in. to 27 ft., Dia in. to ft., Dia in. to ft.
Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No 1255

TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)
(7) PVC

Screen or Perforation Openings Are:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 6 Wire wrapped 8 Saw cut (9) Drilled holes 11 None (open hole)
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

Screen-Perforation Dia 6 in. to 37 ft., Dia in. to ft., Dia in to ft.
Screen-Perforated Intervals: From 27 ft. to 37 ft., From ft. to ft.
From ft. to ft., From ft. to ft.
Gravel Pack Intervals: From ft. to ft., From ft. to ft.
From ft. to ft., From ft. to ft.

5 GROUT MATERIAL: (1) Neat cement 2 Cement grout 3 Bentonite 4 Other
Grouted Intervals: From 3 ft. to 13 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:
1 Septic tank 4 Cess pool 7 Sewage lagoon 10 Fuel storage 14 Abandoned water well
2 Sewer lines 5 Seepage pit 8 Feed yard 11 Fertilizer storage 15 Oil well/Gas well
3 Lateral lines 6 Pit privy 9 Livestock pens 12 Insecticide storage 16 Other (specify below)
(13) Watertight sewer lines

Direction from well South How many feet 30 ? Water Well Disinfected? Yes X No
Was a chemical/bacteriological sample submitted to Department? Yes No X : If yes, date sample was submitted month day year: Pump Installed? Yes No X
If Yes: Pump Manufacturer's name Model No. HP Volts
Depth of Pump Intake ft. Pumps Capacity rated at gal./min.
Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other

6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on 2 month 19 day 81 year, and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 193
This Water Well Record was completed on 6 month 25 day 81 year under the business name of Price Water Well by (signature) John Davenport

7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	brown soil			
2	9	sandy clay			
9	11	fine sand			
11	17	fine gravel			
17	37	medium gravel			

ELEVATION:

Depth(s) Groundwater Encountered 1 21 ft. 2 ft. 3 ft. 4 ft. (Use a second sheet if needed)

INSTRUCTIONS: Use typewriter or ball point pen, *please press firmly* and *PRINT* clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T 23 R 6 E/(W) SEC. 1 Sw ¼ SE ¼ NW ¼