			WATE	R WELL RECORD	Form WWC-5	KSA 82a-	1212		
LOCATIO	N OF WAT	ER WELL:	Fraction		Sec	tion Number	Township Number	Range Number	
County:		eno	SE 1/4		NW _{/4}	1	T 23 S	R 6 EW	
Distance ar	nd direction t	from nearest tov	wn or city street a	address of well if located	within city?			0	
	2617 N. M	ain, Hutchins	on, Kansas						
	WELL OW		T & E Oil #1	8					
IR#, St. Address, Box # : 911 N. Halstead							Board of Agriculture, Division of Water Resources		
	ZIP Code	:	Hutchinson,	Ks. 67501			Application Number:		
LOCATE	WELL'S LC	CATION WITH	4 DEPTH OF C	COMPLETED WELL	. 20	ft. ELEVA	TION:NA		
AN "X" I	N SECTION	BOX:					2		
i [!	-	WELL'S STATIC	WATER LEVEL	.1.163. ft. b	elow land sur	face measured on mo/day/y	, 02-25-94	
Pump test data: Well water was ft. after hours pumping gpm									
	Est. Yield gpm: Well water was ft. after hours pumping								
Bore Hole Diameter 7.5/8 in. to								n. to	
* ~ -	!	1 '	WELL WATER	TO BE USED AS:	5 Public water	r supply	8 Air conditioning 11	Injection well	
ī	- sw	!	1 Domestic	3 Feedlot	6 Oil field wa	ter supply	9 Dewatering 12	Other (Specify below)	
-	- sw	SE	2 Irrigation				Monitoring well		
1 L	_ i _ l	ı	Was a chemical	bacteriological sample s	ubmitted to D	epartment? Ye	es; If ye	s, mo/day/yr sample was sub-	
	\$		mitted				ter Well Disinfected? Yes	No X	
TYPE O	F BLANK C	ASING USED:		5 Wrought iron	8 Concre	ete tile	CASING JOINTS: Glu	ed Clamped	
1 Ste		3 RMP (S	R)	6 Asbestos-Cement		(specify below	,	lded	
(2)PV		4 ABS		7 Fiberglass				eaded. X	
								. in. to ft.	
				in., weight		lbs./		_{No.} sch. 40	
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Ste		3 Stainles		5 Fiberglass		MP (SR)		y)	
2 Brass 4 Galvanized steel			6 Concrete tile			12 None used (d			
SCREEN OR PERFORATION OPENINGS ARE:						8 Saw cut	11 None (open hole)		
1 Continuous slot 2 Louvered shutter 4 Key punched 7 Torch cut							9 Drilled holes		
	uvered shutte			7 Torch			` • • •	toft.	
SCHEEN-F	PERFORATE	D INTERVALS:						toft.	
c	DAVEL DA	CK INTERVALS						toft.	
6 GROUT	MATERIAL	· 1 Neat	cement	2 Cement grout	3 Bento	onite 4	Other	to ft.	
Grout Inter	vals: From	n 0	.ft. to 6 .	ft. From	6 ft.	to. 8	ft. From	ft. toft.	
								Abandoned water well	
What is the nearest source of possible contamination 1 Septic tank 4 Lateral lines				7 Pit privy			storage 15	1	
2 Sewer lines 5 Cess						12 Fertilizer storage		Other (specify below)	
3 Watertight sewer lines 6 Seepa			•				cticide storage		
Direction from well? south							iny feet? 10	00	
FROM	TO		LITHOLOGIC	LOG	FROM	TO		INTERVALS	
0	4	cly, d	k-mod brn, sl	sity, si sndy, damp-r	nøist				
_4	10.3			slty, mod calic clst,					
10.3	20	snd, l	t gy/brn, f-vc,	w/tr-mod grvl, p srt	d, moist				
						4			
							MANA/4O flux	ah maunt aavar	
								sh mount cover	
					-		Site ID 65	DU4	
7 001	I	00.144100111	TDIO OFFICE	TION. TL'		l			
								under my jurisdiction and was	
		/year) 01-3 1		This Water V			ord is true to the best of my on (mo/day/yr)	knowledge and belief. Kansas	
	business na		Core Services,		veli necora w	as completed by (signa	2 4 2	<i>^</i>	
ander the	Dusiness Ha	and or Good	2 3. 3 30. 11000,			by (signa	aluie) Area Ar	V-`	