			WATE	ER WELL RECORD	Form WWC-	5 KSA 82a	1212			
LOCATIO	ON OF WAT	ER WELL:	Fraction			ection Number	Township Numbe	er	Range Number	
County:		no	NE 1/4		NW 1/4	1	T 23	s	R 6 E(W)	
Distance and direction from nearest town or city street address of well if located within city?										
d war-	617 N. M	ain, Hutchinso		_	~~~					
	WELL OW		T & E Oil #18				Decret of Assist		inician of Mater Beauty	
	ddress, Bo	(#:	911 N. Halste				<del>-</del>		ivision of Water Resources	
City, State,			, Hutchinson,	Ks. 67501			Application Nur			
LOCATE WELL'S LOCATION WITH DEPTH OF COMPLETED WELL. 20 ft. ELEVATION: NA										
AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered 1.13ft. 2										
ī	WELL'S STATIC WATER LEVEL11.70 . ft. below land surface measured on mo/day/yr 02-25-94									
	Pump test data: Well water was ft. after hours pumping gpm									
	Est. Yield gpm: Well water was ft. after hours pumping gpm									
•	Bore Hole Diameter 7.5/8in. to									
. w ⊢	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							njection well		
-	I.	1	1 Domestic	3 Feedlot	6 Oil field w	ater supply	9 Dewatering	12 (	Other (Specify below)	
-	- SW	SE	2 Irrigation							
1 1	1 1		, -						mo/day/yr sample was sub-	
1			mitted	- Substantial Subs			ter Well Disinfected?		No X	
5 TYPE C	F BLANK (	ASING USED:	1111100	5 Wrought iron	8 Conc	rete tile			Clamped	
1 Ste		3 RMP (S	(R)	6 Asbestos-Cement		r (specify below			ed	
(2)PV		4 ABS	• • •	7 Fiberglass		, ,	• • • • • • • • • • •		<sub>ded.</sub> X	
(1			in to 10	•						
Blank casing diameter										
		R PERFORATIO		m., weight						
				<i>E E</i> 'hl	(7)P		10 Asbesto			
1 Ste		3 Stainless		5 Fiberglass		MP (SR)				
2 Bra		4 Galvaniz		6 Concrete tile				٠,	en hole)	
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed							8 Saw cut		11 None (open hole)	
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes										
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)   SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft., From ft. to										
SCHEEN-	PERFORATI	ED INTERVALS:								
From.   ft. to   .ft., From   ft. to   .ft.     GRAVEL PACK INTERVALS:   From.   8   ft. to   .20   .ft., From   ft. to   .ft.										
	BRAVEL PA	CK INTERVALS:								
			From							
6 GROUT	MATERIAL		,		3 Ben					
Grout Intervals: From 0 ft. to 6 ft., From 6 ft. to 8 ft., From ft. to ft.										
What is the nearest source of possible contamination:						10 Livestock pens		14 A	pandoned water well	
1 Se	ptic tank	4 Late	ral lines	7 Pit privy		11 Fuel storage			il well/Gas well	
2 Sewer lines 5 Cess			pool 8 Sewage lagoo		oon	12 Fertilizer storage		16 Other (specify below)		
3 Watertight sewer lines 6 Seep						13 Insecticide storage				
Direction f		northy				How ma			300	
FROM	то		LITHOLOGIC	LOG	FROM	ТО	PLUG	GING I	NTERVALS	
-0	5"	asphalt								
5"	4'	cly, dk-mod	brn, sl slty, mo	od sndy, moist						
_4	10.5	cly, it gy/brn	ı, si sity, tr cali	ic, mod plst, moist						
_10.5	13	snd, It brn, f-	-c, p srtd, mois	st						
13	20	snd, It brn, f-	v c w/mod f-r	n grvl, p srtd, sat						
	l									
							MW12	2-flush	mount cover	
							Site ID			
							One is			
7 CONT	DACTOR'S		D'S CEDTIFICA	TIONI. This					In a man a liveria attack a man a	
7 CONTI	on (mo/de	/year) <b>0.13.1</b> :	LOA	HON: This water well w	as (1) const	ructed, (2) rec	onstructed, or (3) plug	gea unc	der my jurisdiction and was	
								-	owledge and belief. Kansas 03-16-94	
under the business name of GeoCore Services, Inc. by (signature)										