

1 LOCATION OF WATER WELL: County: Reno		Fraction SW 1/4 SW 1/4 NE 1/4	Section Number 2	Township Number T 23 S	Range Number R 6 E
Distance and direction from nearest town or city street address of well if located within city? 2401 N. Van Buren Hutchinson					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code : Elmer J. Miller 2401 N. Van Buren Hutchinson Kan. 67502			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 34 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 19 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 19 ft. below land surface measured on mo/day/yr 8-14-92 Pump test data: Well water was 20 ft. after 1 hours pumping 30 gpm Est. Yield 75 gpm Well water was 20 ft. after 6 hours pumping 34 gpm Bore Hole Diameter 9 in. to 20 ft., and 6 in. to 34 ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 0 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 0 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 6 in. to 24 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No. 250 TYPE OF SCREEN OR PERFORATION MATERIAL: 0 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 0 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 24 ft. to 34 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 0 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 3 ft. to 20 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 0 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? West How many feet? 40					
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0	3	Sandy Soil			
3	9	Sandy clay			
9	13	fine sand			
13	19	fine gravel			
19	34	medium gravel			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 0 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-14-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 193 This Water Well Record was completed on (mo/day/yr) 8-14-92 under the business name of Price Water Well Serv. by (signature) John Davenport					