

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Reno</u>	<u>C</u> $\frac{1}{4}$ <u>SE</u> $\frac{1}{4}$ <u>NW</u> $\frac{1}{4}$	<u>2</u>	<u>T</u> <u>23</u> <u>S</u>	<u>R</u> <u>6</u> <u>EW</u>

Distance and direction from nearest town or city street address of well if located within city?

2402 Tyler Hutchinson

2 WATER WELL OWNER: <u>Leon Morris</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>2402 Tyler</u>	Application Number:
City, State, ZIP Code: <u>Hutchinson Kan 67502</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>3.0</u> ft. ELEVATION:	WELL'S STATIC WATER LEVEL: <u>14.14</u> ft. below land surface measured on mo/day/yr <u>7-20-93</u>
	Depth(s) Groundwater Encountered: <u>14.14</u> ft. 2. ft. 3. ft.	Pump test data: Well water was <u>15</u> ft. after <u>1</u> hours pumping <u>30</u> gpm
	Est. Yield: <u>75</u> gpm; Well water was <u>15</u> ft. after <u>6</u> hours pumping <u>30</u> gpm	Bore Hole Diameter: <u>9</u> in. to <u>15</u> ft., and <u>6</u> in. to <u>30</u> ft.
	WELL WATER TO BE USED AS:	
	1 Domestic    3 Feedlot    6 Oil field water supply    9 Dewatering    12 Other (Specify below) 2 Irrigation    4 Industrial    7 Lawn and garden only    10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> ; If yes, mo/day/yr sample was submitted		
Water Well Disinfected? Yes <u>X</u> No		

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter: <u>6</u> in. to <u>20</u> ft., Dia			Threaded
Casing height above land surface: <u>12</u> in., weight			lbs./ft. Wall thickness or gauge No. <u>1.250</u>
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	7 PVC
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	11 None (open hole)
SCREEN-PERFORATED INTERVALS: From <u>20</u> ft. to <u>30</u> ft., From			
GRAVEL PACK INTERVALS: From			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From <u>3</u> ft. to <u>15</u> ft., From				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? <u>South</u>				
How many feet? <u>20</u>				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Sandy soil			
2	9	Sandy clay			
9	13	fine sand			
13	16	fine gravel			
16	30	medium gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7-20-93</u> and this record is true to the best of my knowledge and belief. Kansas	
Water Well Contractor's License No. <u>193</u>	This Water Well Record was completed on (mo/day/yr) <u>6-28-94</u>
under the business name of <u>Price Water Well</u> by (signature) <u>John Dawson</u>	