


1 LOCATION OF WATER WELL: County: Reno		Fraction: S 1/4 NW 1/4 NW 1/4	Section Number: 2	Township Number: T 23 S	Range Number: R 6 E/W
Distance and direction from nearest town or city street address of well if located within city? 2805 Nottingham Hutchinson Kan.					
2 WATER WELL OWNER: RR#, St. Address, Box # : Charles Wall RT3 Hutchinson Kan. City, State, ZIP Code : 67502		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;">  </div>		4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 14 ft. 2. 14 ft. 3. 14 ft. WELL'S STATIC WATER LEVEL 14 ft. below land surface measured on mo/day/yr Pump test data: Well water was 15 ft. after 1 hours pumping 50 gpm Est. Yield 75 gpm; Well water was 15 ft. after 6 hours pumping 30 gpm Bore Hole Diameter 9 in. to 15 ft. and 6 in. to 30 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 6 in. to 20 ft. Dia. in. to 20 ft. Dia. in. to 20 ft. Dia. in. to 20 ft. Casing height above land surface 12 in. weight 1250 lbs./ft. Wall thickness or gauge No. 250 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 20 ft. to 30 ft. From 20 ft. to 30 ft. From 20 ft. to 30 ft. From 20 ft. to 30 ft. GRAVEL PACK INTERVALS: From 20 ft. to 30 ft. From 20 ft. to 30 ft. From 20 ft. to 30 ft. From 20 ft. to 30 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 3 ft. to 15 ft. From 3 ft. to 15 ft. From 3 ft. to 15 ft. From 3 ft. to 15 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? Northeast How many feet? 45					
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0	2	Sandy soil			
2	10	Sandy clay			
10	13	fine sand			
13	16	fine gravel			
16	30	medium gravel			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-10-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 193 This Water Well Record was completed on (mo/day/yr) 2-15-94 under the business name of Price Water well by (signature) John Davenport					