

1 LOCATION OF WATER WELL: Fraction SW 1/4 NE 1/4 SE 1/4 Section Number 3 Township Number T 23 S Range Number R 6 EW
 County: Reno

Distance and direction from nearest town or city street address of well if located within city?

1508 Linwood

2 WATER WELL OWNER: Chris Brown
 RR#, St. Address, Box #: 1508 Linwood
 City, State, ZIP Code: Hutchinson Kan 67502 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 28 ft. ELEVATION:

	Depth(s) Groundwater Encountered 1. <u>11</u> ft. 2. <u>11</u> ft. 3. <u>11</u> ft.
	WELL'S STATIC WATER LEVEL <u>11</u> ft. below land surface measured on mo/day/yr <u>6-19-89</u>
	Pump test data: Well water was <u>12</u> ft. after <u>1</u> hours pumping <u>30</u> gpm
	Est. Yield <u>50</u> gpm: Well water was <u>12</u> ft. after <u>1</u> hours pumping <u>30</u> gpm
Bore Hole Diameter <u>9</u> in. to <u>12</u> ft. and <u>6</u> in. to <u>28</u> ft.	
WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial <u>7</u> Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> <u>X</u> ; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes <u>X</u> No	

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
3 PVC 4 ABS 7 Fiberglass Threaded

Blank casing diameter 6 in. to 18 ft. Dia. in. to 18 ft. Dia. in. to 18 ft. Dia. in. to 18 ft.
 Casing height above land surface 12 in. weight 1250 lbs./ft. Wall thickness or gauge No. 250

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 18 ft. to 28 ft. From 18 ft. to 28 ft. From 18 ft. to 28 ft.
 GRAVEL PACK INTERVALS: From 18 ft. to 28 ft. From 18 ft. to 28 ft. From 18 ft. to 28 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 12 ft. From 12 ft. to 28 ft. From 12 ft. to 28 ft. From 12 ft. to 28 ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage

Direction from well? East How many feet? 25

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Sandy soil			
2	6	sandy clay			
6	10	fine sand			
10	13	fine gravel			
13	28	medium gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-19-89 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 193 This Water Well Record was completed on (mo/day/yr) 6-20-89
 under the business name of Price Water Well by (signature) John Davenport