				IEH WE	LL RECORD	Form W		KSA 82a						
	ON OF WAT	ER WELL:	Fraction		_		Section	n Number	Town	iship Nu	mber	Range	e Numb	ier 🗸
County:	Re	no	NE	1/4 SI	1/4	NW 1/4		3	T	23	S	R		E(W)
Distance a	nd direction	from nearest tov	wn or city stree	et address	of well if locate	ed within o	city?							\sim
			tabinaan K											
2 WATER	124 West 4 Well ow	th Street, Hu												
_			T & E Oil #									Nicialan at V	Mata . D	
•	Address, Box	(#:	P.O. Box 1	303							griculture, [vivision of v	vater H	esources
City, State		· · · · · · · · · · · · · · · · · · ·	, Hutchinson	n, Ks. 67	7504				App	olication	Number:			
LOCATE	WELL'S LO	OCATION WITH	4 DEPTH O	F COMPL	ETED WELL	17		ft. ELEVA	TION:	. NA		<i></i> .		1
- AN "X"	IN SECTION	BOX:	Denth(s) Grou	ındwater	Encountered	1 9		ft 2)		ft 3			ft
- L	- 	' 	MELL'S STA	TIC MALATI	ER LEVEL	0.50	# hala					03-14	-94	
† l	- i - I	- 1 1	l .											
-	- NW -X	NE	P	ump test	data: Well wat	er was .		ft. a	fter		hours pu	nping		. gpm
1 1	i X	1	Est. Yield		gpm: Well wat	er was .		ft. a	fter	<i></i>	hours pu	nping		. gpm
ا ا	i	1	Bore Hole Dia	ameter . 7.	5./8in. to)	1,7	ft., a	and		in.	to	.	ft.
* w -	1	1	WELL WATE	R TO BE	USED AS:	5 Public	water s	upply	8 Air cond	litionina	11	niection we	ell	
- 1	۱ ا	i	1 Domes		3 Feedlot			,	9 Dewater	•		•)W)
I I-	- SW	SE												
	1 1	'	2 Irrigation		4 Industrial				10 Monitori					
1 L			Was a chemic	cal/bacter	ological sample	submitted	to Depa	artment? Ye	esl	No.≏	; If yes,	mo/day/yr	sample	was sub
1	\$		mitted					Wa	ter Well Dis	sinfecte	d? Yes	No.		
5 TYPE C	OF BLANK C	ASING USED:		5 W	rought iron	8 C	oncrete	tile	CASI	NG JOI	NTS: Glued	1 C	lamped	
 1 Ste	eel	3 RMP (SI	B)		sbestos-Cement	9.0	ther (sn	ecify below	v)		Weld	ed		
(2)PV		4 ABS	,	,				•	•			ided. X		
_					berglass									
	-	2										coh		n.
Casing hei	ght above la	nd surface	0	in., v	eight	<u>.</u>		Ibs./	ft. Wall thic	kness o	or gauge N	sch.	.	
TYPE OF	SCREEN OF	R PERFORATIO	N MATERIAL:				7)PVC			10 Asb	estos-ceme	nt		
1 Ste	eel	3 Stainless	s steel	5 Fi	berglass	•	8 RMP	(SR)		11 Othe	er (specify)			
2 Brass 4 Galvanized steel					oncrete tile	9 ABS				None used (open hole)				
		RATION OPENIN									, ,		(open h	volo)
						zed wrapp			8 Saw c			11 None	(open n	ole)
	ntinuous slo					wrapped			9 Drilled	noies				,
2 Lo	uvered shutt	er 4 K	ey punched		7 Torc)			
SCREEN-F	PERFORATE	D INTERVALS:	From	7	ft. to .		1.7 .	ft., Froi	m		ft. t	D		ft.
			From		ft. to .		<i></i> .	ft., From	m		ft. t	o	<i>.</i>	ft.
C	RAVEL PAG	CK INTERVALS:			3 ft. to .									
_			From		ft. to			ft., From						ft.
e CDOLIT	MATERIAL			(a)										
_					nent grout		Bentonit		Other					
Grout Inter	vals: From	n ()	.ft. to 4		ft., From	4	ft. to.	, , , ,	ft., F	rom	· • · · · · ·	ft. to	<i></i>	ft.
What is the	e nearest so	urce of possible	contamination	:				10 Lives	tock pens		14 A	bandoned v	water w	ell
•					7 Pit privy			11)Fuel storage			15 Oil well/Gas well			
2 Sewer lines 5 Cess pool			s nool	8 Sewage lagoo							16 Other (specify below)			
3 Watertight sewer lines 6 Seepage			-				13 Insecticide storage				To Other (specify below)			
	•									100				
Direction f		south						How ma	ny feet?		11001110 1			
FROM	то		LITHOLOG	IC LOG		FRC	M	то		PL	ugging i	VIERVALS	<u> </u>	
0	6"	concrete												
- 6"	1'	snd, It brn, f-	-m, w/sl tr g	rvl, mod	srtd, moist		_							
1	3	cly, v dk brn												
3	7	snd, It brn, f-												
				, moa si		-								
		damp												
<u>7</u>	.17	snd, It brn, f	•	t-m grvi	, p sna,									
		moist	:-sat											
									,,,,,,					
														
											A14 4 67 .			
											N11-flush		cover	<u> </u>
										Sit	e ID 712	17		. 1
		7 211												
7 CONTE	RACTORIS	D I ANDOWNE	D'S CEDTIEIO	ATION: 7	hio water	wa (11)	not-::-1	L	matricat	or (0)	lugged	lor mu lust-	dictic=	and was
		OR LANDOWNE												
completed								ad this ross		- 44 4	a			
												owledge an	10 bellet 17.04	. Nansas
Water Wel		s License No							on (mo/day	/yxh		owiedge an 03-1	17-94	. Narisas