

To BWS 2-21-80

USE TYPEWRITER OR BALL
POINT PEN—PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment—Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Reno	Fraction NW 1/4 NE 1/4 NE 1/4	Section number 3	Township number T 23 S R 6	Range number XW
2. Distance and direction from nearest town or city: 700' West of Hendricks & 30th St. Street address of well location if in city:			3. Owner of well: City of Hutchinson City Building Hutchinson, Kansas 67501 City, state, zip code:			
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 42 in. Completion date 2/1/80 Well depth 82 ft.		
		<p>City Well No. 17</p>		7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
				8. Use: <input type="checkbox"/> Domestic <input checked="" type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
				9. Casing: Material Steel Height: Above xxx in. Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 60 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 70.6 lbs./ft. Dia. 18 in. to 52 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 0.375		
5. Type and color of material		From	To	10. Screen: Manufacturer's name Layne Stainless Type Shutter Dia. 18" Slot/gauze 0.105" Length 30' Set between 52 ft. and 82 ft. Gravel pack? Yes Size range of material 1/8-3/8"		
Top soil		0	3	11. Static water level: 13 ft. below land surface Date 1/11/80		
Brown clay		3	14	12. Pumping level below land surfaces: 36 ft. after 3 hrs. pumping 1500 g.p.m. 2300 g.p.m. Estimated maximum yield 2300 g.p.m.		
Med. coarse to fine gravel		14	80	13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date 1/11/80		
Red shale		80	82	14. Well head completion: <input type="checkbox"/> Pitless adapter <input type="checkbox"/> Inches above grade		
				15. Well grouted? Yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 20 ft.		
				16. Nearest source of possible contamination: 400 ft. Direction E.S.E. Type Septic Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
				17. Pump: Manufacturer's name Layne Not installed Model number 13CHX HP 75 Volts 460 Length of drop pipe 50 ft. capacity 1200 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
18. Elevation:		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Layne Western Co., 102 Business name Wichita, Kansas License No. 2-19-80 Address OK Sodur Date 2-19-80 Signed OK Sodur Authorized representative		
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input type="checkbox"/> Upland <input checked="" type="checkbox"/> Valley						

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

T. 2
W. 1/4
R. 6
S. 23
E. 1/4
Sec. 3
1/4
1/4
1/4
NW NE NE