

1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 SW 1/4 Section Number 3 Township Number T 23 S Range Number R 6 E
 County: Ren

Distance and direction from nearest town or city street address of well if located within city?
1/2 N. Hwy 96 on Pennington Rd W. of Hutchinson

2 WATER WELL OWNER: Charles Borend
 RR#, St. Address, Box #: RR3 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Hutchinson Kan 67501 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N	
NW	NE
SW	SE
S	

4 DEPTH OF COMPLETED WELL 35 ft. ELEVATION: 7-22-82
 Depth(s) Groundwater Encountered 1. 12 ft. 2. 13 ft. 3. 20 ft.
 WELL'S STATIC WATER LEVEL 12 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 13 ft. after 1 hours pumping 20 gpm
 Est. Yield 50 gpm: Well water was 13 ft. after 1 hours pumping 20 gpm
 Bore Hole Diameter 9 in. to 13 ft., and 6 in. to 35 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 6 in. to 25 ft., Dia. 25 in. to 25 ft., Dia. 25 in. to 25 ft.
 Casing height above land surface 12 in., weight 25 lbs./ft. Wall thickness or gauge No. 255
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 25 ft. to 35 ft., From 25 ft. to 35 ft., From 25 ft. to 35 ft.
 GRAVEL PACK INTERVALS: From 25 ft. to 35 ft., From 25 ft. to 35 ft., From 25 ft. to 35 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 13 ft., From 3 ft. to 13 ft., From 3 ft. to 13 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? East How many feet? 100

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	brown soil			
3	9	sandy clay			
9	11	fine sand			
11	14	fine gravel			
14	35	medium gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-22-82 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 193 This Water Well Record was completed on (mo/day/yr) 7-10-83
 under the business name of Price Water Well by (signature) John Davenport

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

23

R

6

E

SEC 3

NW 1/4

NW 1/4

SW 1/4