

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Reno		SE 1/4 NW 1/4 SW 1/4	7	T 23 S	R 6 E
Distance and direction from nearest town or city street address of well if located within city? 1 W 1/4 N 1/4 E 4th st & Whiteside Rd w. of Hutchinson					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # : RR1		Application Number:			
City, State, ZIP Code : Hutchinson Kan 67501					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 38 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 38 ft. below land surface measured on mo/day/yr 6-15-81			
		Pump test data: Well water was 45 ft. after 1 hours pumping 30 gpm			
		Est. Yield 50 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter: 7 in. to 80 ft. and Heat Pump in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply <input checked="" type="checkbox"/> Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <input checked="" type="checkbox"/> No			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
<input checked="" type="radio"/> 2 PVC		4 ABS		6 Asbestos-Cement	
				7 Fiberglass	
Blank casing diameter 6 in. to 65 ft., Dia.				8 Concrete tile	
Casing height above land surface 12 in., weight				9 Other (specify below)	
TYPE OF SCREEN OR PERFORATION MATERIAL:				CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped	
1 Steel		3 Stainless steel		Welded	
2 Brass		4 Galvanized steel		Threaded	
5 Fiberglass		6 Concrete tile		8 RMP (SR)	
8 RMP (SR)		9 ABS		10 Asbestos-cement	
11 Other (specify)		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		8 Saw cut	
1 Continuous slot		6 Wire wrapped		<input checked="" type="radio"/> 9 Drilled holes	
2 Louvered shutter		7 Torch cut		10 Other (specify)	
3 Mill slot				11 None (open hole)	
4 Key punched					
SCREEN-PERFORATED INTERVALS:		From 65 ft. to 80 ft.		ft. to ft.	
		ft. to ft.		ft. to ft.	
GRAVEL PACK INTERVALS:		From 13 ft. to 80 ft.		ft. to ft.	
		ft. to ft.		ft. to ft.	
6 GROUT MATERIAL:					
1 Neat cement		<input checked="" type="radio"/> 2 Cement grout		3 Bentonite	
4 Other					
Grout Intervals: From 3 ft. to 13 ft.		ft. to ft.		ft. to ft.	
What is the nearest source of possible contamination:		10 Livestock pens		14 Abandoned water well	
<input checked="" type="radio"/> 1 Septic tank		7 Pit privy		11 Fuel storage	
2 Sewer lines		8 Sewage lagoon		15 Oil well/Gas well	
3 Watertight sewer lines		9 Feedyard		12 Fertilizer storage	
4 Lateral lines				16 Other (specify below)	
5 Cess pool					
6 Seepage pit					
Direction from well? West		How many feet? 80			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	brown sandy soil			
2	19				
19	22				
22	35				
35	46				
46	65				
65	80	medium gravel			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <input checked="" type="checkbox"/> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-15-81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 193 This Water Well Record was completed on (mo/day/yr) 6-25-82 under the business name of Price Water Well Service by (signature) John Davenport					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

SE 1/4

NW 1/4

SW 1/4