

LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <b>Reno</b>	<b>NE 1/4 SE 1/4 SW 1/4</b>	<b>9</b>	<b>T 23 S</b>	<b>R 6 E</b>

611 Blomville  
WATER WELL OWNER: Rita Frye  
R#, St. Address, Box # : 2820 W. 4th  
City, State, ZIP Code : Hutchinson KS 67501

Board of Agriculture, Division of Water Resources  
Application Number:

Depth(s) Groundwater Encountered 1. 18 ft. 2. 40 ft. 3. 12-9-87 ft.

WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 12-9-87

Pump test data: Well water was 18 ft. after 4 hours pumping 20 gpm

Est. Yield 20 gpm: Well water was 18 ft. after 4 hours pumping 20 gpm

Bore Hole Diameter 8 in. to 40 ft. and 40 in. to 40 ft.

WELL WATER TO BE USED AS:

<input checked="" type="checkbox"/> Domestic	<input type="checkbox"/> 3 Feedlot	<input type="checkbox"/> 6 Oil field water supply	<input type="checkbox"/> 9 Dewatering	<input type="checkbox"/> 11 Injection well
<input type="checkbox"/> 2 Irrigation	<input type="checkbox"/> 4 Industrial	<input type="checkbox"/> 7 Lawn and garden only	<input type="checkbox"/> 10 Observation well	<input type="checkbox"/> 12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes X No       ; If yes, mo/day/yr sample was submitted       

Water Well Disinfected? Yes X No

TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued . . . . . Clamped . . . . .  
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded . . . . .  
2 PVC 4 ABS 7 Fiberglass . . . . . Threaded . . . . .  
blank casing diameter . . . . . 5 in. to 30 ft. Dia . . . . . in. to . . . . . ft. Dia . . . . . in. to . . . . . ft.  
casing height above land surface . . . . . 12 in. weight . . . . . 160 lbs. lbs./ft. Wall thickness or gauge No. . . . .

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify) .....
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	7 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify) .....	

GREEN-PERFORATED INTERVALS: From 30 ft. to 40 ft., From ft. to ft.  
From ft. to ft., From ft. to ft.  
GRAVEL PACK INTERVALS: From 30 ft. to 40 ft., From ft. to ft.  
From ft. to ft., From ft. to ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 18 ft. From ft. to ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

[illegible]

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.