

1 LOCATION OF WATER WELL: County: Reed Fraction: SW 1/4 NE 1/4 SW 1/4 Section Number: 10 Township Number: T 23 Range Number: R 6 EW

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: Gene Fuller RR#, St. Address, Box #: 1010 Washridge City, State, ZIP Code: Wichita KS 67502 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION: 1025 ft.

Depth(s) Groundwater Encountered 1. 15 ft. 2. 18 ft. 3. 10-25 ft.

WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 18 ft. after 4 hours pumping 20 gpm

Est. Yield 20 gpm Well water was 18 ft. after 4 hours pumping 20 gpm

Bore Hole Diameter 9 in. to 30 in. to 30 in. to 30 in.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes Yes No No If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes Yes No No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded

Blank casing diameter 5 in. to 20 in. to 20 in. to 20 in. Dia. 5 in. to 5 in. to 5 in. to 5 in.

Casing height above land surface 19 in., weight 19 lbs./ft. Wall thickness or gauge No. 50R26

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 RMP (SR) 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 20 ft. to 30 ft. From 20 ft. to 30 ft. From 20 ft. to 30 ft. From 20 ft. to 30 ft.

GRAVEL PACK INTERVALS: From 20 ft. to 30 ft. From 20 ft. to 30 ft. From 20 ft. to 30 ft. From 20 ft. to 30 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 20 ft. From 0 ft. to 20 ft. From 0 ft. to 20 ft. From 0 ft. to 20 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? SE How many feet? 100

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 30 Top soil 0 30 Gravel

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-2-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 440 This Water Well Record was completed on (mo/day/yr) 5-28-92 under the business name of Carl Vincent Service by (signature) Carl Vincent

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.