	ell #3			R WELL RECORD	Form WWC-5	KSA 82a-			. 0185508	
		ER WELL:	Fraction	C.C.		tion Number	Township I	Number	Range N	_
	eno		C 1/4		SW 1/4	12	т 23	S	R 6	<u> 50</u> 0
			-	ddress of well if loca	•					
				of 5th and Wa	shington S	treet, H	utchinson,	, KS		
WATER W	ELL OW	•	way Oil Co	•						
RR#, St. Addr	ress, Box		and Washin	gton			Board of	Agriculture, [	Division of Wate	er Resources
City, State, ZII	P Code	: Hutçl	hinson, KS				Application	n Number:		
LOCATE W	ELL'S LO	OCATION WITH 4	DEPTH OF C	OMPLETED WELL.		. ft. ELEVAT	ION:15	31.60		
AN "X" IN S	SECTION	BOX:	⊐ Depth(s) Ground	water Encountered	1. 15.8	ft. 2.		ft. 3		ft.
ī [	1			WATER LEVEL						
I I	1	1	Pumi	o test data: Well wa	iter was	I/A ft aft	er	hours nu	mpina	gom
	۱w	NE		N.A. gpm; Well wa						
<u> </u>	! }		Bore Hole Diame	eter6in. t	30	II. an	nd	in.	to	ff
* w -	<del>;                                    </del>			O BE USED AS:	5 Public water		B Air conditionin		Injection well	
-	i							J	•	holow)
:	sw	SE	1 Domestic	3 Feedlot	6 Oil field wat		9 Dewatering		Other (Specify	
1 1	! ×	<u> </u>	2 Irrigation	4 Industrial	_		Observation v	- 17		
<u> </u>	1 "			bacteriological sample	e submitted to De					V .
			mitted				er Well Disinfect		No	Χ
J TYPE OF E	BLANK C	ASING USED:		5 Wrought iron	8 Concre			DINTS: Glued	i Clamp	oed
1 Steel		3 RMP (SR	)	6 Asbestos-Cemen	t 9 Other (	specify below	)		ed <i></i>	.,
@ PVC		4 ABS		7 Fiberglass					ided	
				ft., Dia						
Casing height	above la	nd surface		.in., weight	<u></u>	Ibs./ft	t. Wall thickness	or gauge No	<sub>o</sub> 40 Sche	adule
TYPE OF SCF	REEN OF	R PERFORATION	MATERIAL:		7 PV	<b>⇒</b>	10 As	bestos-ceme	nt	
1 Steel		3 Stainless	steel	5 Fiberglass	8 RM	P (SR)	11 01	ther (specify)		
2 Brass		4 Galvanize	ed steel	6 Concrete tile	9 ABS		12 No	one used (op	en hole)	
SCREEN OR	PERFOR	ATION OPENING	SS ARE:	5 Gau	zed wrapped		8 Saw cut	` .	11 None (ope	en hole)
1 Contin	uous slot	3 Mil	slot		e wrapped		9 Drilled holes			
2 Louver			y punched		ch cut		10 Other (speci			
		D INTERVALS:		10 ft. to						
OONEENT EN	011/11/	D INTERIVALO.		ft. to						
GDA	\/E! DA/	CK INTERVALS:		6 ft. to						
GHA	VELFA	ON INTERVALS.	From							
6 GROUT MA	ATERIAL	1 Nost se		ft. to		ft., From			-	11.
_				2 Cement grout	3 Bento	nite 4 (	Other			
Grout Intervals				6 ft., From	π. 1				ft. to	
_		urce of possible o				10 Livesto			bandoned wate	
1 Septic		4 Latera		7 Pit privy		11 Fuel s			il well/Gas well	
2 Sewer		5 Cess p		8 Sewage la	igoon		er storage	16 O	ther (specify be	elow)
	•	er lines 6 Seepa		9 Feedyard		13 Insecti	cide storage		asoline S	ra c i on
Direction from		North		200		How man	y feet?	100 ft.		
FROM	то		LITHOLOGIC	LOG	FROM	то		LITHOLOG	IC LOG	
0	2.5	Tan Silty								
2.5	7	Tan Fine S								
	10	Tan Fine to	<u>o Medium S</u>	and						
10	14	Tan Fine to								
14	20			Coarse Sand						
				ocarbon Odor						
20 ;	30			Coarse Sand	and Grave					
,		Wich no Ode		200.00 00110						
		MICH HO CO	V1				,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	_		
				:						
7 CONTRAC	TOR'S	R LANDOWNER	S CERTIFICATI	ON: This water well	was (1) construc	cted (2) recor	nstructed, or (3)	plågged und	er my jurisdicti	on and was
completed on		10	/09/85				d is true to the b			
Water Well Co			410	This Water	Well Record was			-1/02	<i>,</i> 8 <b>5</b>	
under the busi		TCD	RACON CONS	ULTANTS SC,	NC.	by (signati			-1/-	
				E PRESS FIRMLY				e or circle the	correct answe	rs. Send top
three copies to	Kansas	Department of Hea	alth and Environn	nent, Division of Envir						
OWNER and a	retain on	e for your records	<b>3</b> .			•	•			4