

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Reno</u>		<u>NW 1/4 NW 1/4 NE 1/4</u>	<u>12</u>	<u>T 23 S</u>	<u>R 6</u> EW
Distance and direction from nearest town or city street address of well if located within city? <u>1602 N Main Hutchinson</u>					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :		<u>1602 N Main</u> <u>Hutchinson, KS 67502</u>			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 1 <u>30 to basement floor</u> ELEVATION: ft.			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL . . . <u>19</u> ft. below land surface measured on mo/day/yr <u>5-20-89</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter in. to ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
2 PVC		4 ABS		6 Asbestos-Cement	
				7 Fiberglass	
Blank casing diameter <u>6</u> in. to ft., Dia in. to ft., Dia in. to ft.				8 Concrete tile	
Casing height above land surface <u>In Basement</u> in. weight lbs./ft. Wall thickness or gauge No.				9 Other (specify below) <u>Galvanized</u>	
TYPE OF SCREEN OR PERFORATION MATERIAL:				CASING JOINTS: Glued Clamped	
1 Steel		3 Stainless steel		7 PVC	
2 Brass		4 Galvanized steel		8 RMP (SR)	
				9 ABS	
				10 Asbestos-cement	
SCREEN OR PERFORATION OPENINGS ARE:				11 Other (specify)	
1 Continuous slot		3 Mill slot		12 None used (open hole)	
2 Louvered shutter		4 Key punched			
				5 Gauzed wrapped	
				6 Wire wrapped	
				7 Torch cut	
				8 Saw cut	
				9 Drilled holes	
				10 Other (specify)	
SCREEN-PERFORATED INTERVALS:				11 None (open hole)	
From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS:					
From ft. to ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout		3 Bentonite	
4 Other					
Grout Intervals: From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines		7 Pit privy	
2 Sewer lines		5 Cess pool		8 Sewage lagoon	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard	
10 Livestock pens				14 Abandoned water well	
11 Fuel storage				15 Oil well/Gas well	
12 Fertilizer storage				16 Other (specify below)	
13 Insecticide storage					
Direction from well? <u>S</u>				How many feet? <u>10</u>	
FROM		TO		LITHOLOGIC LOG	
FROM		TO		PLUGGING INTERVALS	
0		30'		19'	
		19'		6"	
		6"		top	
				gravel	
				bentonite (below basement floor)	
				cement	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5-20-89</u> and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. <u>447</u> This Water Well Record was completed on (mo/day/yr) <u>6-11-89</u>					
under the business name of <u>Miller Drilling</u> by (signature) <u>Emmiller</u>					