

1 LOCATION OF WATER WELL:		Fraction SE 1/4 SW 1/4 SE 1/4		Section Number 12		Township Number T 23 S		Range Number R 6 EW			
County: Reno											
Distance and direction from nearest town or city street address of well if located within city? 228 East 4th Street, Hutchinson, Ks.											
2 WATER WELL OWNER:		T & E Oil #16				Board of Agriculture, Division of Water Resources					
RR#, St. Address, Box # :		P.O. Box 1303				Application Number:					
City, State, ZIP Code :		Hutchinson, Ks. 67504									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 24 ft. ELEVATION: NA									
		Depth(s) Groundwater Encountered 1. 17 ft. 2. ft. 3. ft.									
		WELL'S STATIC WATER LEVEL 15.79 ft. below land surface measured on mo/day/yr 03-03-94									
		Pump test data: Well water was ft. after hours pumping gpm									
		Est. Yield gpm: Well water was ft. after hours pumping gpm									
		Bore Hole Diameter 7 5/8 in. to 24 ft. and in. to ft.									
		WELL WATER TO BE USED AS:									
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well									
		Was a chemical/bacteriological sample submitted to Department? Yes. No. X ; If yes, mo/day/yr sample was submitted									
		Water Well Disinfected? Yes No X									
5 TYPE OF BLANK CASING USED:											
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded X											
Blank casing diameter 2 in. to 14 ft. Dia in. to ft. Dia in. to ft.											
Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. sch. 40											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)											
SCREEN-PERFORATED INTERVALS: From 14 ft. to 24 ft. From ft. to ft.											
GRAVEL PACK INTERVALS: From 12 ft. to 24 ft. From ft. to ft.											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other											
Grout intervals: From 0 ft. to 10 ft. From 10 ft. to 12 ft. From ft. to ft.											
What is the nearest source of possible contamination:											
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below)											
Direction from well? northeast How many feet? 75											
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
0		6"		concrete							
6"		6'		cly, mod brn, mod slty, mod-tr f							
				grvl, moist							
6		12		snd, lt brn, f-v c, w/mod f grvl, p							
				srt'd, damp							
12		24		snd, v lt brn w/blk stk @ 14', f-v c							
				w/tr f grvl, p srt'd, damp, sat @ 17'							
MW7-flush mount cover Site ID 00071231											
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 03-02-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 03-16-94 under the business name of GeoCore Services, Inc. by (signature) <i>Ralph R. Roll</i>											