

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Reno		SE 1/4 SW 1/4 SE 1/4		12		T 23 S		R 6 EW	
Distance and direction from nearest town or city street address of well if located within city? 228 East 4th Street, Hutchinson, Ks.									
2 WATER WELL OWNER:		T & E Oil #16		Board of Agriculture, Division of Water Resources					
RR#, St. Address, Box # :		P.O. Box 1303		Application Number:					
City, State, ZIP Code :		Hutchinson, Ks. 67504							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 25 ft. ELEVATION: NA							
		Depth(s) Groundwater Encountered 1. 18 ft. 2. . ft. 3. . ft.							
		WELL'S STATIC WATER LEVEL . . . 17.83 ft. below land surface measured on mo/day/yr . . . 03-03-94							
		Pump test data: Well water was . . . ft. after . . . hours pumping . . . gpm							
		Est. Yield . . . gpm: Well water was . . . ft. after . . . hours pumping . . . gpm							
		Bore Hole Diameter: 7 5/8 in. to . . . 25 ft., and . . . in. to . . . ft.							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes . . . No X . . . If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes . . . No X							
5 TYPE OF BLANK CASING USED:									
1 Steel		3 RMP (SR)		5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued . . . Clamped . . .	
2 PVC		4 ABS		6 Asbestos-Cement		9 Other (specify below)		Welded . . .	
				7 Fiberglass				Threaded X . . .	
Blank casing diameter . . . 2 in. to . . . 15 ft., Dia . . . in. to . . . ft., Dia . . . in. to . . . ft.									
Casing height above land surface . . . 0 in., weight . . . lbs./ft. Wall thickness or gauge No. . . sch. 40									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel		3 Stainless steel		5 Fiberglass		7 PVC		10 Asbestos-cement	
2 Brass		4 Galvanized steel		6 Concrete tile		8 RMP (SR)		11 Other (specify) . . .	
						9 ABS		12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot		3 Mill slot		5 Gauzed wrapped		8 Saw cut		11 None (open hole)	
2 Louvered shutter		4 Key punched		6 Wire wrapped		9 Drilled holes			
				7 Torch cut		10 Other (specify) . . .			
SCREEN-PERFORATED INTERVALS: From . . . 15 ft. to . . . 25 ft., From . . . ft. to . . . ft.									
GRAVEL PACK INTERVALS: From . . . 13 ft. to . . . 25 ft., From . . . ft. to . . . ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From . . . 0 ft. to . . . 11 ft., From . . . 11 ft. to . . . 13 ft., From . . . ft. to . . . ft.									
What is the nearest source of possible contamination:									
1 Septic tank		4 Lateral lines		7 Pit privy		11 Fuel storage		14 Abandoned water well	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		12 Fertilizer storage		15 Oil well/Gas well	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		13 Insecticide storage		16 Other (specify below)	
Direction from well? southwest						How many feet? 120			
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS			
0	1	cly, dk brn, v sndy, moist							
1	5	cly, mod brn, mod slty, mod sndy, tr f grvl, moist							
5	7	snd, lt brn, f-c, w sl tr grvl, sl tr cly, damp							
7	15	snd, lt brn, f-c, w/sl-mod f grvl, p srted, damp							
15	25	snd, lt brn, m-c, w/f-m grvl, damp							
MW6-flush mount cover Site ID 00067775									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) . . . and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License 08-02-94 . . . This Water Well Record was completed on (mo/day/yr) . . .									
under the business name of 527 . . . by (signature) <i>Don Roll</i> 03-16-94									