

1 LOCATION OF WATER WELL: County: Reno Fraction: SE 1/4 NW 1/4 NW 1/4 Section Number: 13 Township Number: T 23 Range Number: R 6 EW

Distance and direction from nearest town or city street address of well if located within city?
110 W. 2nd Hutchinson Kan.

2 WATER WELL OWNER: Robert Peel
RR#, St. Address, Box #: 413 N. Main
City, State, ZIP Code: Hutchinson Kan 67501

Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 32 ft. ELEVATION: 10-10-88

Depth(s) Groundwater Encountered 1. 16 ft. 2. 17 ft. 3. 20 ft.

WELL'S STATIC WATER LEVEL 16 ft. below land surface measured on mo/day/yr 10-10-88

Pump test data: Well water was 17 ft. after 1 hours pumping 20 gpm

Est. Yield 50 gpm: Well water was 17 ft. after 1 hours pumping 20 gpm

Bore Hole Diameter 9 in. to 17 ft. and 6 in. to 32 ft.

WELL WATER TO BE USED AS: 5 Public water supply 6 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
7 Fiberglass Threaded X

Blank casing diameter 6 in. to 22 ft. Dia. 22 in. to 250 lbs./ft. Wall thickness or gauge No. 250

Casing height above land surface 12 in., weight 250 lbs./ft.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 7
12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Mill slot 3 Gauzed wrapped 4 Wire wrapped 5 Saw cut 6 None (open hole)
2 Louvered shutter 4 Key punched 7 Torch cut 8 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 22 ft. to 32 ft. From 22 ft. to 32 ft. From 22 ft. to 32 ft. From 22 ft. to 32 ft.

GRAVEL PACK INTERVALS: From 22 ft. to 32 ft. From 22 ft. to 32 ft. From 22 ft. to 32 ft. From 22 ft. to 32 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 2

Grout Intervals: From 0 ft. to 17 ft. From 17 ft. to 32 ft. From 17 ft. to 32 ft. From 17 ft. to 32 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage

Direction from well? East How many feet? 25

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 2 Sandy soil

2 9 Sandy clay

9 13 fine sand

13 17 fine gravel

17 32 medium gravel

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-10-88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 193 This Water Well Record was completed on (mo/day/yr) 11-20-89 under the business name of Price Water Well by (signature) John Davenport

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

2

EW

SEC

 $\frac{1}{4}$ $\frac{1}{4}$

4.