

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Reno		NW 1/4 NE 1/4 SE 1/4	14	T 23 S	R 6 E
Distance and direction from nearest town or city street address of well if located within city?					
2 WATER WELL OWNER: Krause Plow Corp.					
RR#, St. Address, Box # : E & Monroe			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Hutchinson KS 67501			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 76 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 17 ft. 2. . ft. 3. . ft.			
		WELL'S STATIC WATER LEVEL 17 ft. below land surface measured on mo/day/yr 5-10-90			
		Pump test data: Well water was . ft. after . hours pumping . gpm			
		Est. Yield . gpm: Well water was . ft. after . hours pumping . gpm			
		Bore Hole Diameter 6 in. to 76 ft. and . in. to . ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes. . No. X If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes . No X			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped . 2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded . Blank casing diameter 2 in. to 70 ft. Dia . in. to . ft. Dia . in. to . ft.					
Casing height above land surface . in., weight . lbs./ft. Wall thickness or gauge No. .					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) . SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) .					
SCREEN-PERFORATED INTERVALS: From 70 ft. to 76 ft. From . ft. to . ft.					
GRAVEL PACK INTERVALS: From 68 ft. to 76 ft. From . ft. to . ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other .					
Grout Intervals: From 58 ft. to 68 ft. From 300 ft. to 35 ft. From . ft. to . ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? NE How many feet? 300					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	12	Bricks, rocks, concrete & trash			
12	28	Sand & Gravel			
28	32	Clay and sand			
32	76	Sand & Gravel			
72		Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-10-90 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 440 This Water Well Record was completed on (mo/day/yr) 6-17-90					
under the business name of Carl Vincent Service by (signature) Em Vance					