

1 LOCATION OF WATER WELL: County: <u>RENO</u>	Fraction <u>NE 1/4 NW 1/4 NW 1/4</u>	Section Number <u>23</u>	Township Number T <u>23</u> S	Range Number R <u>6</u> E <u>(W)</u>
--	---	-----------------------------	----------------------------------	---

Distance and direction from nearest town or city street address of well if located within city?

1000 Morton Rd. South Hutchinson

2 WATER WELL OWNER: <u>Morton Salt</u> RR#, St. Address, Box # : <u>P.O. Box 1547</u> City, State, ZIP Code : <u>Hutchinson, KS 67504 1547</u>	Board of Agriculture, Division of Water Resources Application Number: <u>RN 003</u>
--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>45</u> ft. ELEVATION:
--	---

	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL <u>17</u> ft. below land surface measured on mo/day/yr <u>2-5-94</u>
	Pump test data: Well water was <u>N/A</u> ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter <u>28</u> in. to <u>45</u> ft., and in. to ft.	
WELL WATER TO BE USED AS:	
1 Domestic	3 Feedlot
2 Irrigation	4 Industrial
5 Public water supply	8 Air conditioning
6 Oil field water supply	9 Dewatering
7 Lawn and garden only	10 Monitoring well
11 Injection well	12 Other (Specify below)
Was a chemical/bacteriological sample submitted to Department? Yes No <u>Y</u> ; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes <u>Y</u> No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>Y</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter <u>16</u> in. to <u>25</u> ft., Dia			11 Other (specify)
Casing height above land surface <u>24</u> in., weight			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS:			
From <u>25</u> ft. to <u>45</u> ft., From			
GRAVEL PACK INTERVALS:			
From <u>20</u> ft. to <u>45</u> ft., From			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From <u>0</u> ft. to <u>20</u> ft., From				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well?				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top Soil			
3	4	Fine Sand			
4	7	Clay Brown			
7	26	Medium Sand + Gravel			
26	28	Green Clay			
28	45	Medium Sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>2-5-94</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>537</u> This Water Well Record was completed on (mo/day/yr) <u>2-5-94</u> under the business name of <u>Flowers Drilling & Pump Service</u> by (signature) <u>Mike Flowers</u>
