


1 LOCATION OF WATER WELL: Fraction SE 1/4 SE 1/4 SW 1/4 Section Number 23 Township Number T 23 S Range Number R 6 W
 County: Reno

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: Doskocil Foods
 RR#, St. Address, Box #: P.O. Box 1570
 City, State, ZIP Code: Hutchinson, KS 67504
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 38.5 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. 11.5 ft. 2. 11.5 ft. 3. 11.5 ft.

WELL'S STATIC WATER LEVEL 11.5 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 11.5 ft. after 11.5 hours pumping 11.5 gpm

Est. Yield 11.5 gpm: Well water was 11.5 ft. after 11.5 hours pumping 11.5 gpm

Bore Hole Diameter 11.5 in. to 11.5 ft., and 11.5 in. to 11.5 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 11.5 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 11.5 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes 11.5 No 11.5; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes 11.5 No 11.5

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued 11.5 Clamped 11.5

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 11.5

11.5 2 PVC 4 ABS 7 Fiberglass Threaded 11.5

Blank casing diameter 11.5 in. to 11.5 ft., Dia 11.5 in. to 11.5 ft., Dia 11.5 in. to 11.5 ft.

Casing height above land surface 11.5 in., weight 11.5 lbs./ft. Wall thickness or gauge No. 11.5

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 11.5

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) 11.5

SCREEN-PERFORATED INTERVALS: From 11.5 ft. to 11.5 ft., From 11.5 ft. to 11.5 ft.

From 11.5 ft. to 11.5 ft., From 11.5 ft. to 11.5 ft.

GRAVEL PACK INTERVALS: From 11.5 ft. to 11.5 ft., From 11.5 ft. to 11.5 ft.

From 11.5 ft. to 11.5 ft., From 11.5 ft. to 11.5 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 11.5

Grout Intervals: From 11.5 ft. to 11.5 ft., From 11.5 ft. to 11.5 ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 11.5 Other (specify below)

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 11.5 Ammonia Refrigeration

Direction from well? West How many feet? 6 ft.

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

38.5 1.5 Bentonite chips 7.26 cu. ft. 38.5 1.5

1.5 0 Concrete 0.29 cu. ft. 1.5 0

0.29

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-29-92 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 4-29-92 This Water Well Record was completed on (mo/day/yr) 4-29-92

under the business name of Robert B. B. B. by (signature) Robert B. B. B.