


LOCATION OF WATER WELL: County: Reno	Fraction NE $\frac{1}{4}$ SW $\frac{1}{4}$ NW $\frac{1}{4}$	Section Number 28	Township Number T 23 S	Range Number R 8W E/W
--	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

2 miles West of Hutchinson, on West 4th, 2 mile south on black top, $\frac{1}{2}$ East, East side.

WATER WELL OWNER: Elpaso Products #4	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: RFD 1	Application Number:
City, State, ZIP Code: Hutchinson, KS 67501	

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 93 ft. ELEVATION: 12 Depth(s) Groundwater Encountered 1. 44 ft. 2. 44 ft. 3. 44 ft. WELL'S STATIC WATER LEVEL 44 ft. below land surface measured on mo/day/yr 4/30/82 Pump test data: Well water was 44 ft. after 44 hours pumping 44 gpm Est. Yield 44 gpm: Well water was 44 ft. after 44 hours pumping 44 gpm Bore Hole Diameter 10 in. to 93 ft., and 93 in. to 93 ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes XX No XX ; If yes, mo/day/yr sample was submitted XX Water Well Disinfected? Yes XX No XX
--	--

TYPE OF CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued XX Clamped XX 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded XX 7 Fiberglass Threaded XX	Blank casing diameter 4 in. to 0 ft., Dia 4 in. to 33 ft., Dia 4 in. to 33 ft. Casing height above land surface 18 in., weight 160 lbs./ft. Wall thickness or gauge No. .750
---	--

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) XX 12 None used (open hole)
--

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) XX
--

SCREEN-PERFORATED INTERVALS: From 33 ft. to 93 ft. From 33 ft. to 93 ft. From 33 ft. to 93 ft. GRAVEL PACK INTERVALS: From 10 ft. to 93 ft. From 10 ft. to 93 ft. From 10 ft. to 93 ft.
--

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other XX Grout Intervals: From 0 ft. to 10 ft. From 0 ft. to 10 ft. From 0 ft. to 10 ft.
--

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Brine pit 13 Insecticide storage 50
--

Direction from well? South	How many feet? 50
-----------------------------------	--------------------------

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	35	Brown Clay			
35	38	Sandy clay			
38	50	Sand with some clay			
50	62	Medium gravel			
62	65	Clay			
65	92	Medium gravel			
92	93	Clay			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/30/82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 4/30/82 Under the business name of Rosencrantz-Bemis Ent. by (signature) Diane Schootness

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.