


Copy - 06

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Reno	NW 1/4 SW 1/4 NW 1/4	28	T 23 S	R 6NE/W

Distance and direction from nearest town or city street address of well if located within city?

2 W of Hutchinson on W. 4th. st., 2 S on Blk. top, 1/2 E, E side.

2 WATER WELL OWNER: Elpaso Products Co. #11	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : RFD 1	Application Number:
City, State, ZIP Code : Hutchinson, KS 67501	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 93 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 37 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 40 ft. below land surface measured on mo/day/yr 7/30/82
	NO Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 8 in. to 93 ft. and in. to ft.
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
	Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 4 in. to 0-40 ft. Dia			11 Other (specify)
Casing height above land surface 18 in. weight 160 lbs./ft. Wall thickness or gauge No. .216			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC		
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 40 ft. to 93 ft.		
	From ft. to ft.		
GRAVEL PACK INTERVALS:	From 10 ft. to 93 ft.		
	From ft. to ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 10 ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	Brine Pit
Direction from well? West			How many feet? 50	

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	5	Top soil and brown clay			
5	25	Brown Clay			
25	35	Brown clay some sand			
35	50	Brown clay			
50	60	Clay and sand			
60	70	Small gravel			
70	75	Small gravel and clay break			
75	90	Small gravel			
90	93	Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/30/82 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 8/3/82
under the business name of Rosencrantz-Bemis Ent. by (signature) Diane Schott

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.