

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: RENO	SE 1/4 NE 1/4 SE 1/4	24	T 23 S	R 6 E/W

Distance and direction from nearest town or city street address of well if located within city?

HUTCHINSON CITY PARK

2 WATER WELL OWNER:	CITY OF HUTCHINSON PARK DEPT. ATT M BURCH
RR#, St. Address, Box #	PO BOX 1567 - HUTCHINSON KS 67504
City, State, ZIP Code	
Board of Agriculture, Division of Water Resources	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	ELEVATION:
	18 ft.	1875 ft.
	Depth(s) Groundwater Encountered 1. 18.25 ft. 2. — ft. 3. — ft.	
	WELL'S STATIC WATER LEVEL 15.25 ft. below land surface measured on mo/day/yr 09-01-94	
	Pump test data: Well water was — ft. after — hours pumping — gpm	
	Est. Yield — gpm: Well water was — ft. after — hours pumping — gpm	
	Bore Hole Diameter 8.625 in. to 18 ft. and — in. to — ft.	
	WELL WATER TO BE USED AS:	
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 <u>Monitoring well</u>	
	Was a chemical/bacteriological sample submitted to Department? Yes — No X ; If yes, mo/day/yr sample was submitted —	
	Water Well Disinfected? Yes — No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued — Clamped —
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 <u>PVC</u>	4 ABS	7 Fiberglass	Welded —
Blank casing diameter 2 in. to 8 ft. Dia — in. to — ft. Dia — in. to — ft.			Threaded X
Casing height above land surface 24 in. weight 5440 lbs./ft. Wall thickness or gauge No. —			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 <u>PVC</u>	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 <u>Mill slot</u>	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 8 ft. to 18 ft. From — ft. to — ft. From — ft. to — ft.			
SAND GRAVEL PACK INTERVALS: From 7 ft. to 18 ft. From — ft. to — ft. From — ft. to — ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 5 ft. From 5 ft. to 3 ft. From 3 ft. to 5 ft. From 5 ft. to — ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage CORRAUTED
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)

Direction from well?	How many feet?
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	
0 5 SOIL - SDV LOAM	
5 18 SAND - FINE TO COARS WITH PIGMENT	
TD 18	

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08-30-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 09-26-94 under the business name of EBERTS DRILLING by (signature) Angela Eberts
--