

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: RENO	SE ¼ NE ¼ SE ¼	24	T 23 S	R 6 EW

Distance and direction from nearest town or city street address of well if located within city?

HUTCHINSON CITY PARK

2 WATER WELL OWNER:	CITY OF HUTCHINSON PARK DEPT. ATT. M. BURCH
RR#, St. Address, Box #	PO BOX 1567- HUTCHINSON KS 67504
City, State, ZIP Code	Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 15.5 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 11.5 ft. 2. - ft. 3. - ft.
	WELL'S STATIC WATER LEVEL 12.22 ft. below land surface measured on mo/day/yr 09-01-94
	Pump test data: Well water was - ft. after - hours pumping - gpm
	Est. Yield - gpm: Well water was - ft. after - hours pumping - gpm
	Bore Hole Diameter 8.625 in. to 15.5 ft., and - in. to - ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 <u>Monitoring well</u>	
Was a chemical/bacteriological sample submitted to Department? Yes - No X ; If yes, mo/day/yr sample was submitted -	
Water Well Disinfected? Yes - No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued - Clamped -
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 <u>PVC</u>	4 ABS	7 Fiberglass	Welded -
Blank casing diameter 2 in. to 5.5 ft., Dia - in. to - ft., Dia - in. to - ft.			Threaded X
Casing height above land surface 0 in., weight SC4 40 lbs./ft. Wall thickness or gauge No. -			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 <u>Mill slot</u>	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:			
From 5.5 ft. to 15.5 ft., From - ft. to - ft.			
From - ft. to - ft., From - ft. to - ft.			
SAND GRAVEL PACK INTERVALS:			
From 4 ft. to 15.5 ft., From - ft. to - ft.			
From - ft. to - ft., From - ft. to - ft.			

6 GROUT MATERIAL:	1 Neat cement	2 <u>Cement grout</u>	3 Bentonite	4 Other -
GROUT INTERVALS:	From 0 ft. to 2 ft.	From 2 ft. to - ft.	From - ft. to - ft.	From - ft. to - ft.
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage <u>CORRELATED</u>	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? -				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	SANDY LOAM			
5	15.5	SAND - FINE - MED COARSE			
TD	15.5				
FULLISH MOUNT WAIVER 08-02-94 DON TAYLOR					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08-31-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 09-26-94
under the business name of EBBERTS DRILLING by (signature) <i>Angela Ebberts</i>