


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Reno		SE 1/4 SE 1/4 SE 1/4	8	T 23 S	R 6 EW
Distance and direction from nearest town or city street address of well if located within city? 2 mi. W of Hutchinson					
2 WATER WELL OWNER:		Mark McKibben			
RR#, St. Address, Box #:		Box 278			
City, State, ZIP Code:		Hutch, KS 67504-0278			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 27 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 9 ft. below land surface measured on mo/day/yr 9-26-94			
		Pump test data: Well water was 12 ft. after 12 hours pumping 30 gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 in. to 30 ft. and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes. No. k; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes k No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued x Clamped			
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded			
2 PVC 4 ABS		7 Fiberglass Threaded			
Blank casing diameter 5 in. to 20 ft. Dia		in. to ft. Dia			
Casing height above land surface 12 in. weight 2.37 lbs./ft. Wall thickness or gauge No. 160					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 20 ft. to 27 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 19 ft. to 30 ft. From ft. to ft.					
6 GROUT MATERIAL:		3 Bentonite 4 Other			
Grout Intervals: From 0 ft. to 19 ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Lake					
Direction from well? W		How many feet? 100			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8	F-M Sandy silt			
8	30	Sand + Gravel			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-26-94 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 447 This Water Well Record was completed on (mo/day/yr) 9-29-94					
under the business name of Miller Drilling by (signature) G. Miller					