LOCATION	OF WATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212 Section Number	T		
		SW 1/4	NW 1/4 SE	1/4	34	Township Number	Range Number	
	rection frem nearest town or cit			1/4	34	T 24 s	R 1W E/W	
4th & Harrison (1/2 W. of Hoover on E. side of Harrison) Sedgwick, KS.								
2 WATER WELL OWNER: CITY OF SEDGWICK								
RR#, ST. ADRESS, BOX#: 511 N. Commercial Board of Agriculture, Divivsion of Water Resource								
CITY, STATE, ZIP CODE: Sedgwick, Kansas Application Number: 960065								
	ELL'S LOCATION WITH	4 DEPTH OF COM		50		EVATION:		
An "X" IN SECTION BOX: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.								
		WELL'S STATIC W.				RFACE MEASURED ON mo/day/yi	05/12/1550	
Pump test data: Well water was ft. after hours pumping								
<u> </u>		Est. Yield Bore Hole Diameter	gpm: Well wa		ft.	after hours p		
w w	E	WELL WATER TO I		Public water :	ft. sunniv		n. to ft. 1 Injection well	
1.1	x	1 Domestic		Oil field wate		•	2 Other (Specify below)	
sw 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well								
I ↓ L		Was a chemical/bacte	riological sample subr	nitted to Dep	artment? Yes	No X ; If yes	s, mo/day/yr sample was	
S submitted Water Well Disinfected? Yes X No								
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped								
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded							***************************************	
2 PVC	4 ABS		7 Fiberglass	SD	R-26		Threaded	
	Diameter 8	in. to 25	ft., Dia	in.	to	ft., Dia in		
Casing height above land surface 12 in., weight 5.594 lbs./ft. Wall thickness or gauge No332 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement								
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)								
2 Brass	4 Galvanized ste	el	6 Concrete tile	9 /	ABS	12 None used	(open hole)	
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)								
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes								
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREEN-PERFORATION INTERVALS: from 25 ft. to 50 ft., From ft. to ft.								
from			ft. t	-	ft., Fron		to ft.	
GRAVEL PACK INTERVALS: from				to 24	ft., Fro			
from ft. to ft., From ft. to ft. GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								
Count Internal Desirable Found								
What is the nearest source of possible contamination:			n. From	n. rom n. to		ft. From ock pens 1	ft. to ft. 4 Abandon water well	
1 Septic tank 4 Lateral lines			7 Pit privy		11 Fuel s	A	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool			8 Sewage lagoon			izer storage	16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent								
Direction from well? How many feet?								
		LITHOLOGIC LOG		FROM	ТО	PLUGGING IN	TERVALS	
0 2 20	topsoil	1				0.00	- 4944	
20 25		ry silty sa	nd					
25 30		medium san				. 100 d 100 % holes	1998	
30 38		to coarse s						
		ith several						
	streaks		_					
38 50) blue sha	ale				11978-14		
—								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and								
was completed on (mo/day/year)								
Well Contractor's License No								
Under the business name of Harp Well & Pump Service. Inc. by (signature)								
Jane Frederick								