I DOCAT	TION OF WA	TED WELL.	FRACTION	Water W	Vell Record	Form WWC-5	KSA 82a-1212	T		
لنا				arer .	CF	,	Section Number	Township Number	Range Number	
Harvey SW 1/4 NW Distance and direction frem nearest town or city street address of well if located with					1/4 SE	1/4	34	T 24 s	R 1W E/W	
4th and Harrison Sedgwick, Kansas										
	TER WELL O				X, Ka	прар				
	ST. ADRESS,		N. Commer					Board of Agrica	ulture, Divivsion of Water Resource	
CITY	, STATE, ZIP		gwick, Kan					Application	n Number: 960105	
		OCATION WITH	4 DEPTH OF CO	MPLETED V	VELL	50	ft. EL	EVATION:		
AN "X'	' IN SECTION	BOX:	Depth(s) ground	water Encoun	tered	1	ft.	2 ft.	3 ft.	
			WELL'S STATIC V				BELOW LAND SU	RFACE MEASURED ON mo/d	^{tау/ут} 03/26/1996	
1	NW	NE	Pump te		Well wat		ft.		rs pumping gpm	
2			Est. Yield	gpm:	Well was		ft.		rs pumping gpm	
M M	-	E	Bore Hole Diameter WELL WATER TO			> 50 Public wate:	ft. r supply	and	in. to ft.	
		k	1 Domestic	BE USED AS 3 Feedlot		rublic wate: Oil field wa		8 Air conditioning 9 Dewatering	11 Injection well 12 Other (Specify below)	
	SW		2 Irrigation	4 Industri		Lawn and g		10 Monitoring well	(open_j)	
			Was a chemical/bac	teriological sa	ımple subn	nitted to De	epartment? Yes	No X ; If	f yes, mo/day/yr sample was	
		S	submitted				•	ter Well Disinfected?	Yes X No	
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped										
1 Stee	ı	3 RMP (SR)			s-Cement	9	Other (Specify l	oelow)	Welded	
2 PVC	2_	4 ABS		7 Fibergla	ass	S	DR-26		Threaded	
ł	sing Diam	•	in. to 25	ft. ,	Dia	in.		ft., Dia	in. to ft.	
	•	e land surface 1		, we	eight 2.		lbs. / ft.	Wall thickness or gauge I 10 Asbesto		
1 Ste		N OR PERFORA 3 Stainless Steel	TION MATERIAL:	5 Fiberglas	88		PVC RMP (SR)			
	1 Steel 3 Stainless Steel 5 Fibergiass 8 RMP (SR) 11 other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
		REFORATION OPI				l wrapped		8 Saw cut	11 None (open hole)	
1	nous slot	GORATION OF 3 Mill si			6 Wire w			9 Drilled holes	· · · · · · · · · · · · · · · · · · ·	
	red shutte				7 Torch c			10 Other (specify)		
SCREE	N-PERFO	RATION INTERV		5		. 50	ft., Fron		ft. to ft.	
from ft. to ft., From									ft. to ft.	
GRAVEL PACK INTERVALS: from 24						50	ft., Fro		ft. to ft.	
<u> </u>			from		ft. t		ft., Fro		ft. to ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug										
Grout Intervals: From 4 ft. to 24 ft. From What is the nearest source of possible contamination:						ft.	to 10 Livest	ft. From ock nens	ft. to ft. 14 Abandon water well	
	ic tank	source or possion 4 Later		7 Pit	7 Pit privy		11 Fuel s	_		
2 Sewe	r lines				vage lagoon	1		izer storage	15 Oil well/Gas well 16 Other (specify below)	
2 Sewer lines 5 Cess pool 8 Sewage 1agot 3 Watertight sewer lines 6 Seepage pit 9 Feedyard								Halda atawara	None Apparent	
ı	n from we	-	-B- I					How many feet?		
FROM			LITHOLOGIC LOC	3		FROM	ТО		INTERVALS	
0	2	topsoil								
2	25	clay	131							
25 33	33 50		ilty sand				+	17 - 14 - 4		
33	30	blue sha	4TG		- :					
							1 1		TANAL CONTRACTOR OF THE PARTY O	
								74.4		
								777.4		
-										
7 000										
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)										
Well Contractor's License No										
Under the business name of HarpWell&PumpServiceInc										
								Vana	e Frederick	